

RG-RAP52-OD Reyeeye Wi-Fi 5 AC1300 Dual-Band Outdoor Access Point




Kode : RG-RAP52-OD
Kategori : Ruijie & Reyeeye Wireless
Harga : Rp 1.072.000,00

RG-RAP52-OD, Reyeeye Wi-Fi 5 AC1300 Dual-Band Outdoor Access Point.

***Belum termasuk adaptor dan poe injector.**

Produk ini merupakan produk Fix Price. Pembelian produk tidak dapat menggunakan diskon apapun.

Penawaran Harga Spesial

 **08112039555**

- AC1300 Wave 2 Outdoor Mesh Mini AP for Villas and Retail Businesses
- Wall or Pole Mounting to Fit in Any Location
- IP65 Weatherproof Rating, Delivering Consistent Protection and Signal Stability
- Detachable Antennas for Customized Coverage Where Needed
- Tailored for Retail Businesses with Reyeeye Mesh, Standalone Portal, and AI Roaming Features



Specification

Model	RG-RAP52-OD
--------------	-------------

Wi-Fi Standards	Wi-Fi 5 (IEEE 802.11ac Wave 2) Wi-Fi 4 (IEEE 802.11n) IEEE 802.11a IEEE 802.11b/g
Max. Transmit Power	CE EIRP: 2.4 GHz to 2.4835 GHz ≤ 20 dBm 5.150 GHz to 5.350 GHz ≤ 23 dBm 5.470 GHz to 5.725 GHz ≤ 30 dBm Note: Country specific restrictions apply
Max Data Rate	2.4 GHz: 400 Mbps 5 GHz: 867 Mbps
Spatial Streams	2.4 GHz: 2x2 MU-MIMO 5 GHz: 2x2 MU-MIMO
Max Throughput	Up to 400 Mbps at 2.4 GHz Up to 867 Mbps at 5 GHz 1.267 Gbps per AP
Fixed Ports	1x10/100/1000 Base-T port
Power Supply	IEEE 802.3af standard PoE power supply 24 V passive PoE power supply
Max. Power Consumption	≤ 14 W
Operating temperature	-30°C - 70°C (-22°F to +158°F) * Long-term operating temperature: -30°C - 65°C (-22°F - 149°F) * Tested short-term operating temperature (Less than 24hours): 66°C - 70°C (150.8°F - 158°F)
Storage temperature	-40°C - 75°C (-40°F to +167°F)
MTBF	>400000H
Maximum number of clients	110
Recommended number of clients	96
Maximum Number of SSIDs	8

[Download Datasheet](#)

* Harga, spesifikasi, dan ketersediaan bisa berubah dan tidak mengikat

URL : <https://www.citraweb.com/produk/1137/>

Informasi lebih lanjut, pemesanan dan pembelian, hubungi: 0274-554444 atau email sales@citraweb.com