

RG-RAP2260(E) REYEE Wi-Fi 6 Multi-G Ceiling Access Point



Kode : RG-RAP2260(E)

Brand : Ruijie - Reyee

Jenis : Wireless Indoor

Harga : Rp 2.582.000,00

RG-RAP2260(E) Ruijie Reyee Wi-Fi 6 Multi-G Ceiling Access Point.

***Belum termasuk adaptor dan poe injector.**

Penawaran Harga Spesial

 **08112039555**

- Build ultra-high performance network with 3202Mbps wireless throughput.
- Client connections over 500, provide higher practical performance for users as well.
- Boost Internet speed with 2.5Gbps uplink.
- Easily install extra AP with Reyee Mesh Tecnology.
- Set up Wi-Fi 6 network in 3 minutes with Ruijie Cloud APP.



Specification

Model	RG-RAP2260(E)
Radio	Dual-stream dual-band
Protocol	Wi-Fi 6 (IEEE 802.11ax) Wi-Fi 5 (IEEE 802.11ac Wave 2/Wave1) Wi-Fi 4(IEEE 802.11n) 802.11a/b/g
Operating Bands	802.11b/g/n : 2.4 GHz - 2.4835 GHz 802.11a/n/ac/ax : 5 GHz: 5.150 GHz - 5.350 GHz, 5.725 GHz - 5.850 GHz (country specific)
Antenna	Built-in Omnidirectional Antennas (2.4 GHz: 3dBi, 5 GHz: 3dBi)
Spatial Streams	2.4 GHz: 4x4 MIMO 5 GHz: 4x4 MIMO
Max Throughput	Up to 800 Mbps at 2.4 GHz Up to 2402 Mbps at 5 GHz 3.202 Gbps per AP
Service Ports	1 x10/100/1000M/2.5G Base-T (PoE In) 1x 10/100/1000M Base-T
Power Supply	Local power supply, DC 12V/1.5A (Note: The power adapter is sold as an optional accessory) 802.3at PoE (Warning: 802.3af or non-standard POE adapter may cause unknown issues. Please use Ruijie POE+ switch or 802.3at POE adapter as power supplier)
Power Consumption	≤ 25.4 W
Operating temperature	0°C - 40°C
Storage temperature	-40°C - 70°C
MTBF	>400000H
Operating Mode	AP mode and routing mode
Maximum number of clients	512
Recommended number of clients	120
Maximum Number of SSIDs	8

[Download Datasheet](#)

* Harga, spesifikasi, dan ketersediaan bisa berubah dan tidak mengikat

URL : <https://www.citraweb.com/produk/1013/>

Informasi lebih lanjut, pemesanan dan pembelian, hubungi: **0274-554444** atau email sales@citraweb.com