

RG-RAP2260(H) Reyee Wi-Fi 6 AX6000 High-density Multi-G Ceiling Access Point



Kode : RG-RAP2260(H)
Kategori : Ruijie & Reyee Wireless
Harga : Rp 3.200.000,00

RG-RAP2260(H) Reyee Wi-Fi 6 AX6000 High-density Multi-G Ceiling Access Point.

***Belum termasuk adaptor dan poe injector.**

- Build ultra-fast and high-density Wi-Fi with 5.95Gbps throughput.
- Client connections over 500, higher practical performance as well.
- Boost Internet speed with 5Gbps uplink for the future.
- Easily install extra AP with Reyee Mesh Tecnology.
- Support standalone captive portal, easy to enable Wi-Fi authentication.



Specification

Model	RG-RAP2260(H)
Protocol	Wi-Fi 6 (IEEE 802.11ax) Wi-Fi 5 (IEEE 802.11ac Wave 2) Wi-Fi 4(IEEE 802.11n) 802.11a/b/g
Operating Bands	802.11b/g/n/ax : 2.400 GHz - 2.4835 GHz 802.11a/n/ac/ax : 5 GHz: 5.150 GHz - 5.350 GHz, 5.470 GHz - 5.725 GHz, 5.725 GHz - 5.850 GHz (country specific)
Antenna	Built-in Omnidirectional Antennas (2.4 GHz: 3dBi, 5 GHz: 4dBi)
Recommended Wi-Fi Coverage Radius	2.4GHz: 40 meters 5GHz: 70 meters The Wi-Fi coverage is related to the installation environment of the access point.
Spatial Streams	2.4 GHz: 4x4 MU-MIMO 5 GHz: 4x4 MU-MIMO
Max Throughput	Up to 1148 Mbps at 2.4 GHz Up to 4804 Mbps at 5 GHz
Service Ports	2 x100/1000/2500 Base-T port 1x DC port 1x Reset button
Power Supply	IEEE 802.3bt PoE DC 48V/1A
Power Consumption	≤ 40 W
Operating temperature	0°C - 40°C
Storage temperature	-40°C - 70°C
MTBF	>400000H
Maximum number of clients	512
Recommended number of clients	130
Maximum Number of SSIDs	8

[Download Datasheet](#)

* Harga, spesifikasi, dan ketersediaan bisa berubah dan tidak mengikat

URL : <https://www.citraweb.com/produk/1015/>

Informasi lebih lanjut, pemesanan dan pembelian, hubungi: 0274-554444 atau email sales@citraweb.com