

# RG-RAP6262 Reyee Wi-Fi 6 AX3000 High-performance Outdoor Omni-directional Access Point



**Kode** : RG-RAP6262  
**Kategori** : Ruijie  
**Harga** : Rp 3.509.000,00

RG-RAP6262 Reyee Wi-Fi 6 AX3000 High-performance Outdoor Omni-directional Access Point. A Perfect Blend of High Performance and Full Coverage with a revolutionary combination of OFDMA and 1024QAM, the latest 802.11ax standard, and the 160MHz band.

Support Extra-Distance Access Point Deployment With gigabit SFP port, the device supports up to 20km transmission from datacenter with single mode fiber.

**\*Belum termasuk adaptor dan poe injector**

- 'UFO' design, a perfect blend of high performance and full coverage
- Enter the era of ultra-high Wi-Fi 6 speed
- Extra-distance access point deployment with SFP port
- IP68 protection, rock-solid in harsh environments
- Easily expand extra outdoor Wi-Fi with Reyee Mesh



### Specification

<b>Model</b>	RG-RAP6262
<b>Protocol</b>	Wi-Fi 6 (IEEE 802.11ax) Wi-Fi 5 (IEEE 802.11ac Wave2) Wi-Fi 4 (IEEE 802.11n) IEEE 802.11a IEEE 802.11b/g
<b>Antenna</b>	Built-in Omnidirectional Antennas (2.4GHz: 3 dBi; 5GHz: 4 dBi)
<b>Spatial Streams</b>	2.4 GHz: 2x2 MU-MIMO 5 GHz: 2x2 MU-MIMO
<b>Max Throughput</b>	Up to 574 Mbps at 2.4 GHz Up to 2402 Mbps at 5 GHz
<b>Service Ports</b>	1x 10/100/1000 Base-T 1x 1GBase-X SFP port 1x DC port 1x Reset button
<b>Power Supply</b>	IEEE 802.3at PoE, DC 12V/2A (Note: The power adapter is sold as an optional accessory)
<b>Power Consumption</b>	≤ 24 W
<b>Operating temperature</b>	-30°C-65°C
<b>Storage temperature</b>	-40°C-85°C
<b>MTBF</b>	>400000H

<b>Maximum number of clients</b>	512
<b>Recommended number of clients</b>	110
<b>Maximum Number of SSIDs</b>	8

[Download Datasheet](#)

\* Harga, spesifikasi, dan ketersediaan bisa berubah dan tidak mengikat

**URL :** <https://www.citraweb.com/produk/1023/>

**Informasi lebih lanjut, pemesanan dan pembelian, hubungi: 0274-554444 atau email [sales@citraweb.com](mailto:sales@citraweb.com)**

[www.citraweb.com](http://www.citraweb.com)