

RG-RAP1260 Reyee Wi-Fi 6 AX3000 Dual-Band Wall Plate Access Point



Kode : RG-RAP1260
Kategori : Ruijie
Harga : Rp 1.840.000,00

RG-RAP1260 Reyee Wi-Fi 6 AX3000 Ultra-Thin Wall Plate Access Point.

***Belum termasuk adaptor dan poe injector.**

Produk ini merupakan produk Fix Price. Pembelian produk tidak dapat menggunakan diskon apapun.

- Dual-radio performance, gigabit wireless wall-mounted AP.
- Better experience with MU-MIMO under 802.11ax.
- Multi-Color changable Cases.
- Easy installation, worldwide compatible.
- Capable of Reyee Mesh and 802.11K/V.
- Powerful Standalone Portal via Ruijie Cloud.

Specification

Model	RG-RAP1260
Wi-Fi Standards	802.11a/n/ac/ax 802.11b/g/n/ax
MIMO	2.4 GHz, 2x2, MU-MIMO 5 GHz, 2x2, MU-MIMO
Max. Data Rate	2.4 GHz: 574 Mbps 5 GHz: 2402 Mbps
Number of Antennas	5
Antenna Type	Built-in omnidirectional antennas
Antenna Gain	2.4 GHz: 3 dBi 5 GHz:: 5 dBi
Transmit Power	EIRP: 26 dBm (2.4 GHz) 26 dBm (5 GHz) (country-specific restrictions apply)
Fixed Ports	1 x 10/100/1000Base-T Ethernet uplink port 4 x 10/100/1000Base-T Ethernet downlink ports 1 x Reset hole
Max. Number of Concurrent STAs	512
Recommended Number of Concurrent STAs	110
Max. Number of SSIDs	8

Supported Frequency Bands	802.11b/g/n/ax: 2.400 GHz to 2.483 GHz 802.11a/n/ac/ax: 5.150 GHz to 5.350 GHz, 5.470 GHz to 5.725 GHz, 5.725 GHz to 5.850 GHz (country-specific restrictions apply)
Channel Bandwidth	2.4 GHz: Auto/20 MHz/40 MHz 5 GHz: Auto/20 MHz/40 MHz/80 MHz/160 MHz
Roaming	Layer 2 roaming Layer 3 roaming 802.11k/v roaming
Security Mode	WAP-PSK, WAP2-PSK, and WPA-WAP2-PSK
Network Access Mode	PPPoE Client DHCP Client Static IP
VLAN	Port-based VLAN VLAN over 802.1Q TV projection screen
LED	1 x System status LED
Reset Hole	1 x Reset hole
Dimensions (W x D x H)	124 mm x 86 mm x 24 mm (4.88 in. x 3.89 in. x 0.94 in.)
Installation Method	In-wall mounting
Power Supply	IEEE 802.3af/at PoE
Max. Power Consumption	12 W
Operating Temperature	0°C to 40°C (32°F to 104°F)
Storage Temperature	-40°C to +70°C (-40°F to +158°F)
Operating Humidity	5% to 95% RH (non-condensing)
Storage Humidity	5% to 95% RH (non-condensing)
Ingress Protection Rating (IP Rating)	IP41
Surge Protection	+/-4kV
MTBF	400,000 hours

[Download Datasheet](#)

* Harga, spesifikasi, dan ketersediaan bisa berubah dan tidak mengikat

URL : <https://www.citraweb.com/produk/1066/>

Informasi lebih lanjut, pemesanan dan pembelian, hubungi: 0274-554444 atau email sales@citraweb.com