

RG-RAP2266 REYEE Wi-Fi 6 AX3000 Indoor Ceiling-Mount Access Point



Kode : RG-RAP2266

Brand : Ruijie - Reyee

Jenis : Wireless Indoor

Harga : Rp 2.064.000,00

RG-RAP2266 Ruijie Reyee Wi-Fi AX3000 Dual-band Round Ceiling AP. Installation With Rotating, Quick and Easy.

***Belum termasuk adaptor dan poe injector**

***Spesifikasi perangkat dijual bisa berbeda dengan yang ditampilkan karena menyesuaikan dengan regulasi di Indonesia.**

Produk ini merupakan produk Fix Price. Pembelian produk tidak dapat menggunakan diskon apapun.

Penawaran Harga Spesial

 **08112039555**

Product Highlights :

- Dual-radio performance, gigabit wireless Ceiling-mounted AP
- Capable of Reyee Mesh and 802.11K/V
- Easy installation, rotating and done
- New circular aesthetics, more in line with the hotel decoration stylex
- Powerful Standalone Portal via Ruijie Cloud



Specification

| | |
|--------------|------------|
| Model | RG-RAP2266 |
|--------------|------------|

| | |
|--|---|
| Wi-Fi Standards | Wi-Fi6 (IEEE 802.11ax) Wi-Fi5 (IEEE 802.11ac Wave 2) Wi-Fi4(IEEE 802.11n) IEEE 802.11a IEEE 802.11b/g |
| MIMO | 2.4GHz: 2x2, MU-MIMO 5GHz: 2x2, MU-MIMO |
| Max. Wi-Fi Speed | 2.4GHz: 574Mbps 5GHz: 2402Mbps |
| Antenna | 5 |
| Antenna Type | Built-In Omnidirectional |
| Antenna Gain | 2.4 GHz: 3.53dBi 5 GHz: 5.15dBi Note The peak gain mentioned above refers to the gain of a single antenna. |
| Transmit Power | EIRP: ≤31dBm (2.4GHz) ≤32.7dBm (5GHz) Country-specific restrictions apply |
| Fixed Ports | 1x10/100/1000 Base-T port 1xDC port 1xReset button |
| Max. Clients | 512 |
| Recommended Clients | 110 |
| Max. SSIDs | 8 |
| Recommended Wi-Fi Coverage Radius | 2.4GHz: 40 meters 5GHz: 70 meters The Wi-Fi coverage is related to the installation environment of the access point |
| Max. Wi-Fi Coverage Radius | 150 meters |
| Operation Frequency Bands | 802.11b/g/n/ax: 2.400 GHz to 2.4835 GHz 802.11a/n/ac/ax: 5.150 GHz to 5.350 GHz, 5.470 GHz to 5.725 GHz, 5.725 GHz to 5.850 GHz country-specific restrictions apply |
| Frequency Bandwidth | 2.4 GHz: Auto/20/40 MHz 5 GHz: Auto/20/40/80/160 MHz |
| Roaming | Layer 2 roaming Layer 3 roaming |
| Security Mode | WPA-PSK, WPA2-PSK, WPA/WPA2-PSK; |
| Network Access Mode | PPPoE Client DHCP Client Static IP |

| | |
|------------------------------|--|
| Dimensions | 220 mm x 220 mm x 52.6 mm (8.66 in. x 8.66 in. x 2.07 in., without the mounting bracket) |
| Installation | Ceiling-Mountable |
| Power Supplies | IEEE 802.3at PoE DC 12V/2A |
| Power Consumption | ≤ 18W |
| Operating Temperature | 0°C to 40°C |
| Storage Temperature | -40°C to 70°C |
| Operating Humidity | 5% to 95% Noncondensing |
| Storage Humidity | 5% to 95% Noncondensing |
| Port Surge | +/-2kV |
| MTBF | >400000H |

[Download Datasheet](#)

* Harga, spesifikasi, dan ketersediaan bisa berubah dan tidak mengikat

URL : <https://www.citraweb.com/produk/1067/>

Informasi lebih lanjut, pemesanan dan pembelian, hubungi: 0274-554444 atau email sales@citraweb.com