

FD1608S-B1 C-DATA 8PON 4COMBO 2SFP+ GPON OLT

Kode : FD1608S-B1

Brand : C-Data

Jenis : FTTH OLT

Harga : Rp 14.000.000,00

Rp 17.970.000,00



GPON OLT FD1608S-B1 CDATA completely meet relative standard of ITU G.984.x and FSAN, which is 1U rack-mounted device with 1 USB interface, 4 uplink GE ports, 4 uplink SFP ports, 2*10GE uplink ports and 8 GPON ports. Each GPON port supports the splitting ratio of 1:128, the GPON system supports up to 1024 terminal connections.

Penawaran Harga Spesial

08112039555

This product meets the requirements in device performance and size of compact server room as the product has high performance and compact size, which convenient and flexible to use, and is easy to deploy as well. Moreover, the product meets the requirements of promoting network performance, improving reliability and reducing power consumption in the perspective of access network and enterprise network and is applicable to three-in-one broadcast television network, FTTP (Fiber to the premise), video monitoring network, enterprise LAN (Local Area Network), internet of things and other network applications with a very high price/performance ratio.



Specification

Model	FD1608S-B1
Uplink Port	COMBO port : 4 10/100/1000M auto-negotiation Ethernet ports 4 SFP interfaces
	10-Gigabit : 2 SFP+ interfaces
PON Port	Quantity : 8
	Physical interface : SFP
	Interface type : ITU-TG.984.2 Class B+/Class C+
	Max splitting ratio : GPON: 1:128
Management Port	1 100/1000BASE-Tx out-band Ethernet port 1 CONSOLE local management port
USB Port	1 USB interface (It's used to backup configuration, upgrade program and record log information)
Transmission distance	20KM
Port rate	GPON: Downstream: 2.5Gbps Upstream: 1.25Gbps
Wavelength	Forwarding: 1490nm Receiving: 1310nm
Interface type	SC/UPC
Fiber type	9/125µm SMF (Single Mode Fiber)
Light transmission power	Class B+ : +1.5?+5dBm Class C+ : +3 ~ +7dBm
Receiving sensitivity	Class B+ : -28dBm Class C+ : -30dBm
Saturation power	Class B+ -8dBm Class C+ -12dBm
Network management method	Support CLI, SNMP, TELNET, SSH, WEB
Business capabilities	<ul style="list-style-type: none"> - Support device log, device upgrade, device management, condition monitoring, configuration management, and user management - Layer 2 switching configuration management: Like port management, VLAN, RSTP, IGMP, ACL, QOS and so on. - PON function configuration management: Like OLT authentication, DBA template, service template, line template and so on. - Layer 3 function: support static routing, dhcp-relay and vlanif configuration.
Backplane Bandwidth	78G

Power supply	220VAC : AC : 100V ~ 240V, 47~63Hz -48DC : DC:-40V ~ -72V BBU (Backup Battery Unit) : DC: 11V ~ 14V Function: When the regular power supply is cut off, it can be switched to the backup power supply, and when the regular power supply resumes, it will switch back to the regular power supply.
Maximum Power	78W
Working temperature	-15 ~ 50 C
Storage temperature	-40 ~ 85 C
Ambient humidity	5 ~ 90% (Non-condensing)

[Download Datasheet](#)

* Harga, spesifikasi, dan ketersediaan bisa berubah dan tidak mengikat

URL : <https://www.citraweb.com/produk/1230/>

Informasi lebih lanjut, pemesanan dan pembelian, hubungi: 0274-554444 atau email sales@citraweb.com