CITRAWEB SOLUSI TEKNOLOGI
www.citraweb.com
info@citraweb.com
sales@citraweb.com

FD514GD-R460 C-DATA 4GE DUAL BAND WIFI XPON ONU



Kode : FD514GD-R460
Brand : C-Data
Jenis : FTTH ONT/ONU/MDU
Harga : Rp 420.000,00
~~Rp 460.000,00~~

FD514GD-R460 CDATA is an indoor fiber broadband access terminal. The device provides one GPON / EPON adaptive optical port and supports XPON mode. It can be used in connection with our company FD16 series GPON OLT or FD11 / 12 series EPON OLT. It can also interconnect with the mainstream manufacture (Huawei / ZTE / Fiberhome) GPON or EPON OLT to provide users with Internet and WIFI services based on GPON and EPON technology.

***Spesifikasi perangkat dijual bisa berbeda dengan yang ditampilkan karena menyesuaikan dengan regulasi di Indonesia.**

Penawaran Harga Spesial
08112039555

www.citraweb.com

- **In compliant with IEEE802.3ah and ITU - T G.984 standard**
- **Support ONU auto-discovery/Link detection/remote upgrade of software**
- **Support SN and LOID+Password multiple registration methods**
- **Support port VLAN configuration**
- **Support port-based rate limitation and bandwidth control**
- **Support MAC address learning**
- **Support MAC address learning account limit**
- **Support VLAN transparent/tag/translate/trunk**
- **Support broadcasting storm resistance function**
- **Support igmp transparent/snooping/proxy mode**
- **Support Dynamic Bandwidth Allocation (DBA)**
- **Support AES encryption and decryption**
- **EMS network management based on SNMP ,convenientfor maintenance**
- **Support power-off alarm function, easy for link problem detection**
- **Support Firewall**
- **Support MAC address/URL filter**
- **Support remote WEB/Telnet access control**
- **Single-fiber access, provides internet, WIFI multiple service.**

Specification

Model	FD514GD-R460

CITRAWEB SOLUSI TEKNOLOGI
www.citraweb.com
info@citraweb.com
sales@citraweb.com

User Port (LAN)	4*10/100/1000Mbps adaptive Ethernet port Full/half duplex Auto MDI/MDI-X
Indicators	PWR / PON / LOS / LAN / INT / WIFI
PON Mode	EPON : 1000BASE-PX20+ symmetric GPON : FSAN G.984.2 standard,Class B+
PON Rate	EPON : 1.25Gbps (downstream/upstream) GPON : 2.488Gbps/1.244Gbps (downstream/upstream)
Wavelength	Transmit : 1310nm Receiver : 1490nm
Receiving sensitivity	EPON : -27dBm GPON : -28dBm
Saturated power	EPON : -3dBm GPON : -8dBm
Transmitting power	EPON : 0 ~ 4dBm GPON : 0.5 ~ 5dBm
WIFI	IEEE802.11b/g/n(2.4G) Max rate: 300M MAX TX power : 17dBm IEEE802.11a/n/ac(5G) Max rate: 867Mbps MAX TX power : 17dBm
Power	External 12VDC/1A power supply adapter
Power consumption	≤9.7W
Working temperature	0 to 40ºC
Operating humidity	10% to 90%(Non-condensing)

Download Datasheet

** Harga, spesifikasi, dan ketersediaan bisa berubah dan tidak mengikat*

URL : https://www.citraweb.com/produk/1234/

Informasi lebih lanjut, pemesanan dan pembelian, hubungi: 0274-554444 atau email sales@citraweb.com

www.citraweb.com