

# FD514GS1-R550 4GE DUAL BAND WIFI6 (AX1500) XPON ONU



**Kode** : FD514GS1-R550  
**Kategori** : C-DATA & PON Accessories  
**Harga** : Rp 470.000,00

FD514GS1-R550 is WiFi6 xPON Gateway ONT, it support 802.11a/b/g/n/ac/ax standards over 2.4GHz and 5GHz, max speed can up to 1500Mbps. FD514GS1-R550 have a high reliability and provide quality of service guarantee, easy management, flexible expansion and networking. It fully meets the ITU-T and IEEE technical standards and have good compatibility with third party OLT.

Penawaran Harga Spesial  
 08112039555

## Specification

<b>Model</b>	FD514GS1-R550
<b>User Port (LAN)</b>	4* 10/100/1000Mbps adaptive Ethernet port Full/half duplex Auto MDI/MDI-X
<b>Indicators</b>	PWR / PON / LOS / LAN1-4 / INT / WIFI
<b>PON Mode</b>	EPON : 1000BASE-PX20+ symmetric GPON : FSAN G.984.2 standard, Class B+ Connector : UPC (Blue)
<b>PON Rate</b>	EPON : 1.25Gbps (downstream/upstream) GPON : 2.488Gbps/1.244Gbps (downstream/upstream)
<b>Wavelength</b>	Transmit : 1310nm Receiver : 1490nm
<b>Receiving sensitivity</b>	EPON : -27dBm GPON : -28dBm
<b>Saturated power</b>	EPON : -3dBm GPON : -8dBm
<b>Transmitting power</b>	EPON : 0 ~ 4dBm GPON : 0.5 ~ 5dBm

<b>WIFI</b>	IEEE802.11b/g/n(2.4G) 2.4G: 40Mhz bandwidth maximum rate 300Mbps 2.4G EIRP : 24dBm  IEEE802.11a/n/ac/ax(5G) 5G: 80Mhz bandwidth maximum rate 1201Mbps 5 G EIRP : 22dBm  Total wireless rate is 1500Mbps
<b>Power</b>	External 12VDC/1A power supply adapter
<b>Power consumption</b>	≤12W
<b>Working temperature</b>	0 to 40°C
<b>Operating humidity</b>	10% ~ 90% (Non-condensing)

[Download Datasheet](#)

\* Harga, spesifikasi, dan ketersediaan bisa berubah dan tidak mengikat

**URL :** <https://www.citraweb.com/produk/1237/>

**Informasi lebih lanjut, pemesanan dan pembelian, hubungi: 0274-554444 atau email [sales@citraweb.com](mailto:sales@citraweb.com)**