

FD514GS1-R550 C-DATA 4GE DUAL BAND WIFI6 (AX1500) XPON ONU



Kode : FD514GS1-R550

Brand : C-Data

Jenis : FTTH ONT/ONU/MDU

Harga : Rp 410.000,00

Rp 470.000,00

FD514GS1-R550 C-Data is WiFi6 xPON Gateway ONT, it support 802.11a/b/g/n/ac/ax standards over 2.4GHz and 5GHz, max speed can up to 1500Mbps. FD514GS1-R550 have a high reliability and provide quality of service guarantee, easy management, flexible expansion and networking. It fully meets the ITU-T and IEEE technical standards and have good compatibility with third party OLT.

***Spesifikasi perangkat dijual bisa berbeda dengan yang ditampilkan karena menyesuaikan dengan regulasi di Indonesia.**

Penawaran Harga Spesial

 08112039555

Specification

Model	FD514GS1-R550
User Port (LAN)	4* 10/100/1000Mbps adaptive Ethernet port Full/half duplex Auto MDI/MDI-X
Indicators	PWR / PON / LOS / LAN1-4 / INT / WIFI
PON Mode	EPON : 1000BASE-PX20+ symmetric GPON : FSAN G.984.2 standard, Class B+ Connector : UPC (Blue)
PON Rate	EPON : 1.25Gbps (downstream/upstream) GPON : 2.488Gbps/1.244Gbps (downstream/upstream)
Wavelength	Transmit : 1310nm Receiver : 1490nm
Receiving sensitivity	EPON : -27dBm GPON : -28dBm
Saturated power	EPON : -3dBm GPON : -8dBm
Transmitting power	EPON : 0 ~ 4dBm GPON : 0.5 ~ 5dBm

WIFI	IEEE802.11b/g/n(2.4G) 2.4G: 40Mhz bandwidth maximum rate 300Mbps 2.4G EIRP : 24dBm IEEE802.11a/n/ac/ax(5G) 5G: 80Mhz bandwidth maximum rate 1201Mbps 5 G EIRP : 22dBm Total wireless rate is 1500Mbps
Power	External 12VDC/1A power supply adapter
Power consumption	≤12W
Working temperature	0 to 40°C
Operating humidity	10% ~ 90% (Non-condensing)

[Download Datasheet](#)

* Harga, spesifikasi, dan ketersediaan bisa berubah dan tidak mengikat

URL : <https://www.citraweb.com/produk/1237/>

Informasi lebih lanjut, pemesanan dan pembelian, hubungi: 0274-554444 atau email sales@citraweb.com