

# FD514GB-X-R410 4GE XPON ONU (MDU)



**Kode** : FD514GB-X-R410  
**Kategori** : C-DATA & PON Accessories  
**Harga** : Rp 435.000,00

FD514GB-X-R410 is an indoor fiber broadband access terminal. The device provides one GPON / EPON adaptive optical port and supports XPON mode. It can be used in connection with our company FD16/17 series GPON OLT or FD12 / 13 series EPON OLT. It can also interconnect with the mainstream manufacture (Huawei / ZTE / Fiberhome) GPON or EPON OLT to provide users with Internet service based on GPON and EPON technology.

- In compliant with IEEE802.3ah and ITU - T G.984 standard
- Support ONU auto-discovery/Link detection/remote upgrade of software
- Support SN and LOID+Password multiple registration methods
- Support port-based rate limitation and bandwidth control
- Support Dynamic Bandwidth Allocation (DBA)
- EMS network management based on SNMP ,convenient for maintenance
- Support power-off alarm function, easy for link problem detection
- Single-fiber access, provides internet service.

## Specification

|                              |   |
|------------------------------|---|
| <b>Model</b>                 | FD514GB-X-R410  |
| <b>User Port (LAN)</b>       | 4x 10/100/1000Mbps adaptive Ethernet port<br>Full/half duplex<br>Auto MDI/MDI-X           |
| <b>Indicators</b>            | PWR / PON / LOS / LAN / RSV   |
| <b>PON Mode</b>              | EPON : 1000BASE-PX20+ symmetric<br>GPON : FSAN G.984.2 standard,Class B+                  |
| <b>PON Rate</b>              | EPON : 1.25Gbps (downstream/upstream)<br>GPON : 2.488Gbps/1.244Gbps (downstream/upstream) |
| <b>Wavelength</b>            | Transmit : 1310nm<br>Receiver : 1490nm  |
| <b>Receiving sensitivity</b> | EPON : -27dBm<br>GPON : -28dBm  |
| <b>Saturated power</b>       | EPON : -3dBm<br>GPON : -8dBm  |
| <b>Transmitting power</b>    | EPON : 0 ~ 4dBm<br>GPON : 0.5 ~ 5dBm  |

|                              |                            |
|------------------------------|----------------------------|
| <b>Operating temperature</b> | -30 to 65°C                |
| <b>Operating humidity</b>    | 10% ~ 90% (Non-condensing) |

[Download Datasheet](#)

\* Harga, spesifikasi, dan ketersediaan bisa berubah dan tidak mengikat

**URL :** <https://www.citraweb.com/produk/1242/>

**Informasi lebih lanjut, pemesanan dan pembelian, hubungi: 0274-554444 atau email [sales@citraweb.com](mailto:sales@citraweb.com)**

[www.citraweb.com](http://www.citraweb.com)