CITRAWEB SOLUSI TEKNOLOGI
www.citraweb.com
info@citraweb.com
sales@citraweb.com

FD5024B C-DATA 24GE XPON ONU (MDU)



Kode : FD5024B
Brand : C-Data
Jenis : FTTH ONT/ONU/MDU
Harga : Rp 2.650.000,00

FD5024B CDATA xPON MDU products are specially designed for FTTB/FTTO/POL application scenarios, providing multi-port data services based on xPON network. The product provides 1G/EPON adaptive PON port for uplink, 24* 10/100/1000BASE-T ports for downlink.

- **Comply with IEEE802.3ah and ITU - T G.984 standard**
- **Support ONU auto-discovery/Link detection/software remote upgrade**
- **Support multiple registration methods of SN and LOID+Password**
- **Support WEB/CLI/SNMP management**
- **Support Dynamic Bandwidth Allocation (DBA)**
- **Support AES encryption and decryption**
- **Support broadcasting storm resistance function**
- **Support IGMP/MLD Snooping**
- **Support ACL control**
- **Support MAC address learning**
- **Support port-based speed limit**
- **Support port flow-control**
- **Support loop detect**
- **Support VLAN/VLAN Stacking/QINQ**

Specification

Model	FD5024B
User Port (LAN)	24x 10/100/1000Mbps adaptive Ethernet port Full/half duplex Auto MDI/MDI-X
Indicators	PWR / PON / SYS / LOS / LAN
PON Mode	EPON : 1000BASE-PX20+ symmetric GPON : Class B+/Class C+
PON Rate	EPON : 1.25Gbps (downstream/upstream) GPON : 2.488Gbps/1.244Gbps (downstream/upstream)
Wavelength	Transmit : 1310nm Receiver : 1490nm

www.citraweb.com

Receiving sensitivity	EPON : -27dBm GPON : -28dBm
Saturated power	EPON : -3dBm GPON : -8dBm
Transmitting power	EPON : 0 ~ 4dBm GPON : 0.5 ~ 5dBm
Power Supply	Maximum machine power consumption : 30W
Working temperature	-10 to 50ºC
Ambient humidity	10% ~ 90% (Non-condensing)

Download Datasheet

** Harga, spesifikasi, dan ketersediaan bisa berubah dan tidak mengikat*

URL : https://www.citraweb.com/produk/1244/

Informasi lebih lanjut, pemesanan dan pembelian, hubungi: 0274-554444 atau email sales@citraweb.com

www.citraweb.com