

# RG-NIS2100-4GT2SFP-HP 6-Port Cloud Managed Industrial Switch 1PoE++ 3PoE+ 2SFP Uplink Ports



**Kode** : RG-NIS2100-4GT2SFP-HP

**Kategori** : Ruijie & Reyee Switch

**Harga** : Rp 1.534.000,00

RG-NIS2100-4GT2SFP-HP, 6-Port Cloud Managed Layer 2 Industrial Switch, with 1 x PoE++ Port, 3 x PoE+ Ports, and 2 x SFP Uplink Ports.

**Produk ini merupakan produk Fix Price. Pembelian produk tidak dapat menggunakan diskon apapun.**

Penawaran Harga Spesial

 **08112039555**

- Industrial-Grade Features Ensure Stable Operation Between -40C and +75C
- IP40 Protection Against 1 mm Solid Particles
- 6kV Surge Protection Against Voltage Spikes
- 90W PoE Output: Perfect for High-Power Device
- Instant ERPS Configuration and Rapid Service Failover Ensure Network Stability
- Ruijie Cloud: Easy Remote Management Anytime, Anywhere



## Specification

|              |   |
|--------------|---|
| <b>Model</b> | RG-NIS2100-4GT2SFP-HP   |
| <b>Ports</b> | 4x 10/100/1000BASE-T Ports (4x PoE/PoE+ ; 1x PoE/PoE+/PoE++)<br>2x SFP 1G |

|  |   |
|--|---|
| <b>Max. PoE budget</b>                       | default : 108W<br>web reserved adjustable interface MAX : 180W          |
| <b>Extend Mode (Long-Range Transmission)</b> | support (port 3-4)  |
| <b>Switching capacity</b>                    | 12 Gbps   |
| <b>Forwarding rate</b>                       | 8.9 Mpps  |
| <b>MAC address table</b>                     | 8000  |
| <b>VLAN</b>                                  | 16  |
| <b>Dimensions (W x D x H)</b>                | 50 mm x 155 mm x 130 mm   |
| <b>Jumbo Frame (MTU)</b>                     | 10000 Bytes   |
| <b>MTBF</b>                                  | > 200,000   |
| <b>Layer type</b>                            | Layer 2   |
| <b>Port surge</b>                            | Common mode: 6 kV   |
| <b>Power Consumption</b>                     | Less than 12W with no PoE load<br>Less than 192W with PoE full load     |
| <b>Power supply</b>                          | DC input<br>Rated voltage range: 46-57V<br>DC Rated current range: 4.2A |
| <b>Fan</b>                                   | Fanless   |
| <b>Operating temperature</b>                 | -40 to 75°C   |
| <b>Storage Temperature</b>                   | -40 to 85°C   |
| <b>Operating humidity</b>                    | 10% to 90% RH   |
| <b>Storage Humidity</b>                      | 5% to 95% RH  |
| <b>Corrosion Protection</b>                  | Salt Tolerance  |
| <b>Mounting</b>                              | DIN-rail Mounting<br>Wall-mount   |
| <b>Terminal Block</b>                        | pin 12&56:Power1 and Power2 input<br>pin 34:Alarm                       |

[Download Datasheet](#)

\* Harga, spesifikasi, dan ketersediaan bisa berubah dan tidak mengikat

**URL :** <https://www.citraweb.com/produk/1271/>

**Informasi lebih lanjut, pemesanan dan pembelian, hubungi: 0274-554444 atau email [sales@citraweb.com](mailto:sales@citraweb.com)**