

# RG-RAP72Pro REYEE Wi-Fi 7 BE5040 Dual-Band Ceiling Access Point



**Kode** : RG-RAP72Pro

**Brand** : Ruijie - Reeye

**Jenis** : Wireless Indoor

RG-RAP72Pro Ruijie Reeye Wi-Fi 7 BE5040 Dual-Band Ceiling Access Point.

**\*Belum termasuk adaptor dan poe injector**

**\*Spesifikasi perangkat dijual bisa berbeda dengan yang ditampilkan karena menyesuaikan dengan regulasi di Indonesia.**

**Produk ini merupakan produk Fix Price. Pembelian produk tidak dapat menggunakan diskon apapun.**

Penawaran Harga Spesial

 **08112039555**

## Product Highlights :

- Next-generation performance with Wi-Fi 7, delivering extra-high wireless speeds
- Superior streaming with Wi-Fi 7's exclusive MLO feature
- Compact design and easy installation
- Enhanced data transmission with 4K-QAM for faster speeds
- Ideal for integrating with enterprise switches to create a robust office network



## Specification

<b>Model</b>	RG-RAP72Pro
--------------	-------------

<b>Wi-Fi Standards</b>	Wi-Fi 4: IEEE 802.11a/b/g/n Wi-Fi 5: IEEE 802.11ac Wave 2 Wi-Fi 6: IEEE 802.11ax Wi-Fi 7: IEEE 802.11be
<b>Spatial Streams</b>	2.4GHz, 2x2 MU-MIMO 5GHz, 3x3 MU-MIMO
<b>Data Rate</b>	Max. throughput: 5011Mbps 2.4 GHz: 688Mbps 5 GHz: 4323Mbps
<b>Antenna</b>	Built-in Antenna gain: 2.4 GHz, 2.0 dBi; 5 GHz, 3 dBi
<b>Channel Width</b>	2.4 GHz: Auto/20/40 MHz 5 GHz: Auto/20/40/80/160 MHz
<b>Transmit Power</b>	2400-2483.5 MHz, EIRP ≤ 27 dBm 5150-5350 MHz, EIRP ≤ 23 dBm 5725-5825 MHz, EIRP ≤ 23 dBm
<b>Service Ports</b>	1 x 10/100/1000BASE-T port 1 x 10/100/1000/2500BASE-T port
<b>Max. Clients</b>	512
<b>Recommended Clients</b>	110
<b>Max. SSIDs</b>	8
<b>Operating Mode</b>	AP mode and router mode
<b>Dimensions</b>	208mm x 208mm x 40mm (8.19in. x 8.19in. x 1.57in.)(excluding the mounting bracket)
<b>Installation</b>	Ceiling-mount or wall-mount
<b>Power Supplies</b>	IEEE 802.3at standard PoE or DC (12 V, 2.5 A)power supply
<b>Power Consumption</b>	≤ 30W
<b>Operating Temperature</b>	0°C to 40°C
<b>Storage Temperature</b>	-40°C to 70°C
<b>Operating Humidity</b>	5% to 95% Noncondensing
<b>Storage Humidity</b>	5% to 95% Noncondensing
<b>Surge Protection</b>	+/-2kV
<b>MTBF</b>	>400000H

[Download Datasheet](#)

\* Harga, spesifikasi, dan ketersediaan bisa berubah dan tidak mengikat

**URL :** <https://www.citraweb.com/produk/1272/>

**Informasi lebih lanjut, pemesanan dan pembelian, hubungi: 0274-554444 atau email [sales@citraweb.com](mailto:sales@citraweb.com)**

[www.citraweb.com](http://www.citraweb.com)