

RG-RAP72Pro REYEE Wi-Fi 7 BE5040 Dual-Band Ceiling Access Point



Kode : RG-RAP72Pro
Brand : Ruijie - Reeye
Jenis : Wireless Indoor
Harga : Rp 2.700.000,00


RG-RAP72Pro Ruijie Reeye Wi-Fi 7 BE5040 Dual-Band Ceiling Access Point.

***Belum termasuk adaptor dan poe injector**

***Spesifikasi perangkat dijual bisa berbeda dengan yang ditampilkan karena menyesuaikan dengan regulasi di Indonesia.**

Produk ini merupakan produk Fix Price. Pembelian produk tidak dapat menggunakan diskon apapun.

Penawaran Harga Spesial

 **08112039555**

Product Highlights :

- Next-generation performance with Wi-Fi 7, delivering extra-high wireless speeds
- Superior streaming with Wi-Fi 7's exclusive MLO feature
- Compact design and easy installation
- Enhanced data transmission with 4K-QAM for faster speeds
- Ideal for integrating with enterprise switches to create a robust office network



Specification

| | |
|--------------|-------------|
| Model | RG-RAP72Pro |
|--------------|-------------|

| | |
|------------------------------|--|
| Wi-Fi Standards | Wi-Fi 4: IEEE 802.11a/b/g/n Wi-Fi 5: IEEE 802.11ac Wave 2 Wi-Fi 6: IEEE 802.11ax Wi-Fi 7: IEEE 802.11be |
| Spatial Streams | 2.4GHz, 2x2 MU-MIMO 5GHz, 3x3 MU-MIMO |
| Data Rate | Max. throughput: 5011Mbps 2.4 GHz: 688Mbps 5 GHz: 4323Mbps |
| Antenna | Built-in Antenna gain: 2.4 GHz, 2.0 dBi; 5 GHz, 3 dBi |
| Channel Width | 2.4 GHz: Auto/20/40 MHz 5 GHz: Auto/20/40/80/160 MHz |
| Transmit Power | 2400-2483.5 MHz, EIRP ≤ 27 dBm 5150-5350 MHz, EIRP ≤ 23 dBm 5725-5825 MHz, EIRP ≤ 23 dBm |
| Service Ports | 1 x 10/100/1000BASE-T port 1 x 10/100/1000/2500BASE-T port |
| Max. Clients | 512 |
| Recommended Clients | 110 |
| Max. SSIDs | 8 |
| Operating Mode | AP mode and router mode |
| Dimensions | 208mm x 208mm x 40mm (8.19in. x 8.19in. x 1.57in.)(excluding the mounting bracket) |
| Installation | Ceiling-mount or wall-mount |
| Power Supplies | IEEE 802.3at standard PoE or DC (12 V, 2.5 A)power supply |
| Power Consumption | ≤ 30W |
| Operating Temperature | 0°C to 40°C |
| Storage Temperature | -40°C to 70°C |
| Operating Humidity | 5% to 95% Noncondensing |
| Storage Humidity | 5% to 95% Noncondensing |
| Surge Protection | +/-2kV |
| MTBF | >400000H |

[Download Datasheet](#)

* Harga, spesifikasi, dan ketersediaan bisa berubah dan tidak mengikat

URL : <https://www.citraweb.com/produk/1272/>

Informasi lebih lanjut, pemesanan dan pembelian, hubungi: 0274-554444 atau email sales@citraweb.com

www.citraweb.com