

# V1600GS-F V-SOL 1PON GPON OLT

**Kode** : V1600GS-F

**Brand** : V-Sol

**Jenis** : FTTH OLT

**Harga** : Rp 3.300.000,00

Rp 3.550.000,00



V1600GS-F vsol is a box-type GPON OLT with one PON port. The price of V1600GS-F is very attractive and the performance is very strong. The splitting ratio of its PON port is 1:128, and the farthest transmission distance is 20KM. Its uplink and downlink bandwidth is as high as: 1.25Gbps/2.5Gbps. V1600GS-F can be widely used in FTTH, SOHO, small business office and other application scenarios.

**1\*GPON, 2\*RJ45+1\*SFP/SFP+.**
**\*Sudah termasuk 1x SFP 8dBm**

Penawaran Harga Spesial

 **08112039555**


V1600GS-F with Fan

**Specification**

<b>Model</b>	V1600GS-F
<b>Uplink Port</b>	QTY : 3
	RJ45(1G) : 2
	SFP(1G)/SFP+(10G) : 1

<b>GPON Port</b>	QTY : 1
	Fiber Type : 9/125µm SM
	Connector : SC/UPC, Class C++/C+++ Class C++ : TX>6.5dBm, Sen: -32dBm Class C+++ : TX>7.5dBm, Sen: -33dBm
	GPON port speed Upstream : 1.244Gbps Downstream : 2.488Gbps
	Wavelength TX : 1490nm RX : 1310nm
	Max splitting ratio : 1:128
	Transmission Distance : 20KM
<b>Management Port</b>	1*USB-COM(Type-C) port
<b>Backplane Bandwidth (Gbps)</b>	16
<b>Port Forwarding Rate(Mpps)</b>	23.808
<b>Management Mode</b>	WEB/Telnet/CLI/SNMP
<b>Lightning Protection Level</b>	Power supply : 4KV Device Interface : 1KV
<b>Power supply</b>	AC : Working Voltage Range: 100~240V, Rated Voltage: 110V/220V DC : 12V/2A
<b>Working temperature</b>	-20 ~ +60 C
<b>Storage temperature</b>	-40 ~ +70 C
<b>Relative Humidity</b>	5 ~ 95% (Non-condensing)
<b>Dimension (L*W*H)</b>	210 x 173 x 43.6 mm

[Download Datasheet](#)

\* Harga, spesifikasi, dan ketersediaan bisa berubah dan tidak mengikat

URL : <https://www.citraweb.com/produk/1289/>

Informasi lebih lanjut, pemesanan dan pembelian, hubungi: 0274-554444 atau email [sales@citraweb.com](mailto:sales@citraweb.com)