

# V1600GT V-SOL 2PON GPON OLT

**Kode** : V1600GT

**Brand** : V-Sol

**Jenis** : FTTH OLT

**Harga** : Rp 6.250.000,00

Rp 7.450.000,00



The V1600GT vsol is a box-type GPON OLT with two GPON ports that meets flexible and fast FTTx access, suiting the scenarios such as sparse/remote/cost-sensitive area, smart industrial park, commercial building and FTTH, etc.

**2\*GE(RJ45)+2\*GE(SFP)/10GE(SFP+)**
**\*Sudah termasuk 2x SFP 9dBm**

Penawaran Harga Spesial

 **08112039555**

## Specification

<b>Model</b>	V1600GT
<b>Uplink Port</b>	QTY : 4
	RJ45(1G) : 2
	SFP(1G)/SFP+(10G) : 2
<b>GPON Port</b>	QTY : 2
	Physical Interface : SFP Slots
	Supported PON module level : Class C++/Class C+++ /Class C++++
	Max splitting ratio : 1:128
<b>Management Port</b>	1*10/100/1000 BASE-T out-band port, 1*CONSOLE port, 1*USB-COM, 1*USB2.0
<b>Backplane Bandwidth (Gbps)</b>	208
<b>Port Forwarding Rate(Mpps)</b>	40.176

<b>PON Port Specification (Class C+++)</b>	Transmission Distance : 20KM
	PON port speed : Upstream 1.244Gbps Downstream 2.488Gbps
	Wavelength TX 1490nm RX 1310nm
	Connector : SC/UPC
	Fiber Type : 9/125µm SMF
	TX Power : +4.5~+10dBm
	Rx Sensitivity : ≤ -30dBm
	Saturation Optical Power : -12dBm
<b>Power supply</b>	AC : Working Voltage Range: 100~240V, Rated Voltage: 110V/220V DC : 48V
<b>Management Mode</b>	WEB , Telnet , CLI
<b>Working temperature</b>	-20 ~ +60 C
<b>Storage temperature</b>	-40 ~ +70 C
<b>Relative Humidity</b>	5 ~ 95% (Non-condensing)
<b>Dimension (L*W*H)</b>	442 x 200 x 43.6 mm

[Download Datasheet](#)

\* Harga, spesifikasi, dan ketersediaan bisa berubah dan tidak mengikat

**URL :** <https://www.citraweb.com/produk/1290/>

**Informasi lebih lanjut, pemesanan dan pembelian, hubungi: 0274-554444 atau email [sales@citraweb.com](mailto:sales@citraweb.com)**