V2802DAC V-SOL 1XPON 2GE DUAL BAND WIFI5 ONU



Kode : V2802DAC
Brand : V-Sol
Jenis : FTTH ONT/ONU/MDU
Harga :
1 - 19 : Rp 420.000,00
20 - ... : Rp 360.000,00

V2802DAC vsol (2GE+WiFi5 XPON ONT) is designed to meet the FTTH requirements of fixed network operators. The ONT is based on a high-performance chipset (Realtek) technology solution, supporting IEEE802.11b/g/n/ac WIFI technology and other Layer 2/Layer 3functions.The ONT supports the OAM/OMCI protocol, and we can configure or manage various services of the ONT on the VSOL OLT.

2*GE+WiFi5
***Spesifikasi perangkat dijual bisa berbeda dengan yang ditampilkan karena menyesuaikan dengan regulasi di Indonesia.**

Penawaran Harga Spesial
08112039555

Key Features :

- **Detect and exchange PON mode automatically**
- **Support EasyMesh protocol**
- **WiFi5 Dual Band 1200Mbps**
- **IPv4/IPv6 Stack**

Specification

Model	V2802DAC
PON Interface	1XPON port(EPON PX20+ and GPON Class B+) SC single mode, SC/UPC connector TX optical power: 0?+4dBm RX sensitivity: -27dBm Overload optical power: -3dBm(EPON) or -8dBm(GPON) Transmission distance: 20KM Wavelength: TX 1310nm, RX1490nm
Wifi Interface	Compliant with IEEE802.11b/g/n/ac WiFi : 2.4GHz 2×2, 5.8GHz 2×2, 5dBi antenna, rate up to 1.167Gbps Multiple SSID TX power: 2.4GHz: 23dBm; 5GHz: 24dBm RX power: 2.4GHz: HT40-MCS7 -72dBm; 5GHz: VHT80 MCS9 <-62dBm

www.citraweb.com

CITRAWEB SOLUSI TEKNOLOGI
www.citraweb.com
info@citraweb.com
sales@citraweb.com

User interface	2×GE, Auto-negotiation, RJ45 ports
O&M	OAM/OMCI, Telnet, WEB, TR069 Support full management of HGU functions by VSOL OLT
Connect Mode	Support bridge, router & bridge/router mixed mode
QoS	Support 4 queues Support SP, WRR, 802.1P and DSCP
Data Service Functions	• Full speed non-blocking switching • 2K MAC address table • 8 full range VLAN ID • Support VLAN tag, untag, transparent, trunk, translation mode • Integrated port monitoring, port mirroring, port rate limiting, port SLA, etc • Support auto polarity detection of Ethernet ports (AUTO MDIX) • Support IGMP v1/v2/v3 snooping/proxy and MLD v1/v2 snooping/proxy
Wireless	• Integrated 802.11b/g/n/ac • Authentication : WEP/WAP-PSK(TKIP)/WAP2-PSK(AES) • Modulation type : DSSS, CCK and OFDM • Encoding scheme : BPSK, QPSK, 16QAM and 64QAM • Easymesh
L3	• IPv4, IPv6 and IPv4/IPv6 dual stack • DHCP/PPPOE/Static • Static route, DHCP Server • NAT/DMZ/DDNS/Virtual Server
Security	• Support Firewall • Support Mac filter Based on MAC or URL • Support ACL
Dimension	178mm×120mm×30mm(L×W×H)
Power adapter	DC 12V, 1.0A, external AC-DC power adaptor
Power supply	≤12W
Operating condition	Operating temp : -10 ~ +55C Operating humidity : 5 ~ 95% (non-condensing)
Storing condition	Storing temp: -40 ~ +70C Storing humidity: 5 ~ 95% (non-condensing)
Indicators	PWR, PON, LOS, WAN, LAN1, LAN2, 2.4G, 5G

www.citraweb.com

Download Datasheet

** Harga, spesifikasi, dan ketersediaan bisa berubah dan tidak mengikat*

URL : https://www.citraweb.com/produk/1298/

Informasi lebih lanjut, pemesanan dan pembelian, hubungi: 0274-554444 atau email sales@citraweb.com