

# V2802GW V-SOL 1XPON 1GE 1FE WIFI4 ONU


**Kode** : V2802GW

**Brand** : V-Sol

**Jenis** : FTTH ONT/ONU/MDU

**Harga** :


1 - 19 : Rp 250.000,00

20 - ... : Rp 245.000,00

V2802GW (1GE+1FE+WiFi 4 XPON ONT) VSOL is specially designed for different FTTH solutions. The ONT is based on a high-performance chipset technology solution, supporting IEEE802.11b/g/n WIFI technology and other Layer 2/Layer 3 functions, and can provide data services for carrier-grade FTTH applications.

**1\*GE+1FE+WiFi4**

Penawaran Harga Spesial

 **08112039555**
**Key Features :**

- **High Performance Solution**
- **XPON Dual Mode Automatically Access to EPON/GPON**
- **WiFi IEEE802.11b/g/n 2T2R 5dBi Antenna**
- **Powerful Firewall**

**Specification**

Model	V2802GW
<b>PON Interface</b>	<ul style="list-style-type: none"> <li>• 1XPON port (EPON PX20+ and GPON Class B+)</li> <li>• SC single mode, SC/UPC connector</li> <li>• TX optical power : 0~+4dBm</li> <li>• RX sensitivity : -27dBm</li> <li>• Overload optical power : -3dBm(EPON) or -8dBm(GPON)</li> <li>• Transmission distance : 20KM</li> <li>• Wavelength : TX 1310nm, RX1490nm</li> </ul>
<b>Wifi Interface</b>	<ul style="list-style-type: none"> <li>• Compliant with IEEE802.11b/g/n</li> <li>• Operating frequency : 2.400-2.4835GHz</li> <li>• support MIMO, rate up to 300Mbps</li> <li>• 2T2R, 2 external antenna 5dBi</li> <li>• Support : multiple SSID</li> <li>• Channel : 13</li> <li>• Modulation type : DSSS, CCK and OFDM</li> <li>• Encoding scheme : BPSK, QPSK, 16QAM and 64QAM</li> </ul>

<b>User interface</b>	1*GE+1*FE, Auto-negotiation RJ45 ports
<b>PON mode</b>	XPON Dual Mode , Can access mainstream EPON/GPON OLTs
<b>Uplink Mode</b>	Bridging and Routing Mode
<b>Alarm</b>	Support Dying Gasp, Port Loop Detect and Eth Port Los
<b>VLAN</b>	<ul style="list-style-type: none"> <li>• 4K VLAN</li> <li>• VLAN tag, untag, transparent, trunk, translation mode</li> </ul>
<b>Multicast</b>	<ul style="list-style-type: none"> <li>• Max Multicast Group 64</li> <li>• IGMPv1/v2/v3/Proxy/Snooping, MLDv1/v2</li> </ul>
<b>QoS</b>	<ul style="list-style-type: none"> <li>• Support 4 queues</li> <li>• Support SP, WRR, 802.1P and DSCP</li> </ul>
<b>L3</b>	<ul style="list-style-type: none"> <li>• DHCP/PPPOE/Static IP, NAT</li> <li>• DHCPv6 Server, IPv4/IPv6 Static route</li> <li>• IPv4/IPv6 dual stack</li> </ul>
<b>WiFi</b>	<ul style="list-style-type: none"> <li>• Authentication : WEP/WAP-PSK(TKIP)/WAP2-PSK(AES)</li> <li>• Multiple SSID and SSID conceal</li> <li>• Wireless channel selection</li> </ul>
<b>Security</b>	<ul style="list-style-type: none"> <li>• Flow &amp; Storm control, Loop Detection</li> <li>• Filtering Based on ACL/MAC/URL</li> </ul>
<b>Management</b>	<ul style="list-style-type: none"> <li>• CTC OAM 2.1 and 3.0</li> <li>• ITUT984 x OMCI</li> <li>• EMSWEBTelnetCLI and unified network management of VSOL OLT</li> </ul>
<b>Dimension</b>	185mm×120mm×34mm(L×W×H)
<b>Power adapter</b>	DC 12V, 1A, external AC-DC power adaptor
<b>Power supply</b>	≤7W
<b>Operating condition</b>	Operating temp : -10 ~ +55C Operating humidity : 5 ~ 95% (non-condensing)
<b>Storing condition</b>	Storing temp: -40 ~ +70C Storing humidity: 5 ~ 95% (non-condensing)
<b>Indicators</b>	POWER, LOS, PON, GE, FE, WiFi

[Download Datasheet](#)

\* Harga, spesifikasi, dan ketersediaan bisa berubah dan tidak mengikat

**URL :** <https://www.citraweb.com/produk/1299/>

**Informasi lebih lanjut, pemesanan dan pembelian, hubungi: 0274-554444 atau email [sales@citraweb.com](mailto:sales@citraweb.com)**