

# PoE Adapter (15W) UNIFI



**Kode** : U-PoE  
**Brand** : Ubiquiti  
**Jenis** : Power Adaptor  
**Harga** : Rp 155.000,00

An adapter that can power UniFi PoE devices, reduce dependency on PoE switch power, and provide a Gigabit LAN connection.

**Produk ini merupakan produk Fix Price. Pembelian produk tidak dapat menggunakan diskon apapun.**

Penawaran Harga Spesial

 08112039555

- Delivers up to 15W of PoE
- Surge, peak pulse, and overcurrent protection
- Contains RJ45 data input, AC cable with earth ground, and PoE output
- LED indicator for status monitoring

## Specification

<b>Dimensions</b>	86 x 46 x 33 mm (3.4 x 1.8 x 1.3")
<b>Output Voltage</b>	48V DC @ 0.32A
<b>Rated Voltage</b>	100—240V AC @ 50/60Hz
<b>Gigabit LAN Port</b>	Yes
<b>2-pair Powering</b>	Pins 4, 5 (+) and 7, 8 (-)
<b>AC Connector</b>	IEC-320 C6
<b>Clamping Protection</b>	11V Data, 60V Power
<b>Data In / PoE</b>	RJ45 Shielded Socket
<b>Input Current</b>	500mA Max.
<b>Inrush Current</b>	<100A peak at 25°C
<b>Efficiency</b>	84.25+%
<b>Switching Frequency</b>	65 kHz
<b>Output Ripple</b>	200mV pp
<b>Line Regulation</b>	≤ 3%

<b>Load Regulation</b>	≤ 5%
<b>Max. Surge Discharge</b>	1500A (8/20 μs) power
<b>Peak Pulse Current</b>	36A (10/1000 μs) data
<b>Response Time</b>	<1 ns
<b>Shunt Capacitance</b>	<5 pF data
<b>Surge Protection</b>	Difference and common mode
<b>Ambient Storage Temperature</b>	-30 to 70°C (-22 to 158° F)
<b>Ambient Operating Temperature</b>	0 to 40° C (32 to 104° F)
<b>Ambient Operating Humidity</b>	10 to 95% noncondensing
<b>Certifications</b>	CE, FCC, IC, UL, CCC

\* Harga, spesifikasi, dan ketersediaan bisa berubah dan tidak mengikat

**URL :** <https://www.citraweb.com/produk/1394/>

**Informasi lebih lanjut, pemesanan dan pembelian, hubungi: 0274-554444 atau email [sales@citraweb.com](mailto:sales@citraweb.com)**