

# Cloud Gateway Ultra UBIQUITI

**Kode** : UCG-Ultra

**Brand** : Ubiquiti

**Jenis** : Router Desktop

**Harga** : Rp 2.310.000,00



**UCG-Ultra** Compact Cloud Gateway with 30+ UniFi device / 300+ client support, 1 Gbps IPS routing, and multi-WAN load balancing.

**Produk ini merupakan produk Fix Price. Pembelian produk tidak dapat menggunakan diskon apapun.**

Penawaran Harga Spesial

 **08112039555**



## Spesifikasi

|                                     |                  |
|-------------------------------------|------------------|
| <b>Model</b>                        | UCG-Ultra        |
| <b>Managed UniFi Devices</b>        | 30+              |
| <b>Simultaneous Users Connected</b> | 300+             |
| <b>Max. WAN Port Count</b>          | 4                |
| <b>Default WAN Ports</b>            | (1) 2.5 GbE RJ45 |

|                                      |   |
|--------------------------------------|---|
| <b>Port Layout</b>                   | 4x (1G/100M/10M)<br>1x (2.5G/1G/100M/10M) |
| <b>IDS/IPS Throughput</b>            | 1 Gbps                                    |
| <b>MAC Address Table Size</b>        | 2,000                                     |
| <b>Max. Power Consumption</b>        | 6.2W                                      |
| <b>Power Method</b>                  | USB type C (5V DC/3A)                     |
| <b>Power Supply</b>                  | USB type C (5V DC/3A) (Adapter included)  |
| <b>Supported Voltage Range</b>       | 100-240V AC                               |
| <b>Heat Dissipation</b>              | 21 BTU/hr                                 |
| <b>Processor</b>                     | Quad-core ARM Cortex-A53 at 1.5 GHz       |
| <b>System Memory</b>                 | 3 GB                                      |
| <b>On-board Storage</b>              | 16 GB                                     |
| <b>Enclosure Material</b>            | Polycarbonate                             |
| <b>Management</b>                    | Ethernet<br>Bluetooth                     |
| <b>Button</b>                        | (1) Factory reset                         |
| <b>Ambient Operating Temperature</b> | -10 to 40° C (14 to 104° F)               |
| <b>Ambient Operating Humidity</b>    | 5 to 95% noncondensing                    |
| <b>Certifications</b>                | CE, FCC, IC, Anatel: 04653-24-08356, SRRC |

\* Harga, spesifikasi, dan ketersediaan bisa berubah dan tidak mengikat

**URL :** <https://www.citraweb.com/produk/1512/>

**Informasi lebih lanjut, pemesanan dan pembelian, hubungi: 0274-554444 atau email [sales@citraweb.com](mailto:sales@citraweb.com)**