CITRAWEB SOLUSI TEKNOLOGI
www.citraweb.com
info@citraweb.com
sales@citraweb.com

RG-NBS3300-16MG4XS-HP RUIJIE REYEE 16-Port Muti-Gigabit 4 Port PoE++ 12 Port PoE+ Layer 2 Managed Sw

Kode : RG-NBS3300-16MG4XS-HP
Brand : Ruijie - Reyee
Jenis : Switch Managed POE



RG-NBS3300-16MG4XS-HP, 16-Port Muti-Gigabit Layer 2 Managed Switch dengan 4x PoE++ Ports, 12x PoE+ Ports, and 4x SFP+ Uplink Ports.

Penawaran Harga Spesial
08112039555

- **Port 2.5 Gbps** menembus batas gigabit standar dan memaksimalkan potensi penuh dari *Access Point* (AP) Wi-Fi 6/7.
- **Port PoE++ standar 802.3bt/at/af** dengan total daya suplai mencapai 370 W.
- **Fitur CPP** melindungi CPU dari serangan siber, memastikan performa dan stabilitas sistem tetap terjaga.
- **Kualitas kelas *enterprise*** yang menjamin performa tinggi dan keandalan perangkat.
- **Berbagai kebijakan keamanan** terintegrasi untuk memberikan perlindungan menyeluruh pada jaringan Anda.
- **Manajemen Cloud yang mudah** untuk pengelolaan praktis kapan saja dan di mana saja.

www.citraweb.com

Spesifikasi

Model	RG-NBS3300-16MG4XS-HP
Product Category	Layer 2+
Number of 10/100/1000/2500BASE-T ports	16
Number of 10GE SFP+ ports	4
PoE Out standard	Ports 1–4: PoE/PoE+/PoE++ (IEEE 802.3af/at/bt) Ports 5–16: PoE/PoE+ (IEEE 802.3af/at)

CITRAWEB SOLUSI TEKNOLOGI
www.citraweb.com
info@citraweb.com
sales@citraweb.com

PoE Budget	370 W
Power input	220 V AC power supply: - Rated input voltage: 100 V AC to 240 V AC, 50/60 Hz - Maximum input voltage: 90 V AC to 264 V AC, 47 Hz to 63 Hz - Maximum input current: 6 A
Maximum power consumption	40 W (with no PoE load) 460 W (with full PoE load)
Power supply	Fixed
RAM	512 MB
Flash Memory	256 MB
Switching capacity	160 Gbps
Forwarding rate	119.04 Mpps
MAC address table	16000
VLAN	4094
Dimensions (W x D x H)	440 mm x 267.5 mm x 43.6 mm
Jumbo Frame (MTU)	9216
MTBF	400,000
Port surge	Service port: ±6 kV for common mode Power connector: ±6 kV for both common mode and differential mode
Fan	2x Fixed
Operating temperature	0°C to 50°C (32°F to 122°F)
Storage Temperature	-40°C to 70°C (-40°F to 158°F)
Operating humidity	10% to 90% RH
Storage Humidity	5% to 95% RH
Certificate	CE, RoHS

www.citraweb.com

Download Datasheet

** Harga, spesifikasi, dan ketersediaan bisa berubah dan tidak mengikat*

URL : https://www.citraweb.com/produk/1520/

Informasi lebih lanjut, pemesanan dan pembelian, hubungi: 0274-554444 atau email sales@citraweb.com