

RG-RAP62-Wall-Lite RUIJIE REYEE Wi-Fi 6 AX3000 Dual-Band Wall-Plate AP

**Kode** : RG-RAP62-Wall-Lite**Brand** : Ruijie - Reyee**Jenis** : Wireless Indoor**Harga** : Rp 1.395.000,00

Ruijie Reyee RG-RAP62-Wall-Lite AX3000 Wave 2 Dual band (2.4GHz&5GHz) wall-mount access points, 2x2 MU-MIMO, Max. 8 SSID, 2x10/1000Mbps LAN Ports (PoE-In) 803af/at PoE, Max power consumption 11.2 W. Support Beamforming, Layer2/3/AI roaming, WPA2, Router mode, Captive portal, Cloud/Eweb/APP management.

***Belum termasuk adaptor dan poe injector**

***Spesifikasi perangkat dijual bisa berbeda dengan yang ditampilkan karena menyesuaikan dengan regulasi di Indonesia.**

Produk ini merupakan produk Fix Price. Pembelian produk tidak dapat menggunakan diskon apapun.

Penawaran Harga Spesial

 **08112039555**

- Kecepatan Wi-Fi 6 AX3000 maksimal 2401Mbps pada 5 GHz dan maksimal 573 Mbps pada 2.4 GHz
- 2 x 1GE LAN Port
- Ultra-thin design dengan ketebalan 24.8 mm
- Kompatibel untuk 86-mm dan EU Standard Junction Boxes
- Manajemen terpusat pada Ruijie Cloud



Spesifikasi

Model	RG-RAP62-Wall-Lite
--------------	--------------------

Wi-Fi Standards	2.4GHz Wi-Fi 4 (IEEE 802.11b/g/n) Wi-Fi 6 (IEEE 802.11ax) 5GHz Wi-Fi 4 (IEEE 802.11a/n) Wi-Fi 5 (IEEE 802.11ac) Wi-Fi 6 (IEEE 802.11ax)
Max. Transmit Power	2400–2483.5 MHz, EIRP ≤27 dBm 5150–5350 MHz, EIRP ≤23 dBm 5725–5825 MHz, EIRP ≤23 dBm
Max Data Rate	2.4 GHz: 573 Mbps 5 GHz: 2401 Mbps
Spatial Streams	2.4 GHz: 2 x 2, MU-MIMO 5 GHz: 2 x 2, MU-MIMO
Antennas	Integrated 2.4 GHz and 5 GHz: 2 built-in omnidirectional antennas
Number of 10/100/1000BASE-T ports	2
Power Supply	PoE/PoE+
PoE In standard	IEEE 802.3af (PoE) IEEE 802.3at (PoE+)
Max. Power Consumption	11.2 W
Operating temperature	0°C to 40°C (32°F to 104°F)
Storage temperature	-40°C to +70°C (-40°F to +158°F)
Operating humidity	5% RH to 95% RH (non-condensing)
Storage humidity	5% RH to 95% RH (non-condensing)
Surge protection	Ethernet port: ±2 kV for common mode
Mounting options	Junction box
MTBF	400.000 hours
Maximum number of associated wireless clients	64 (2.4 GHz) 256 (5 GHz) 256 (2.4 GHz and 5 GHz enabled)

Recommended number of clients	Support for IEEE 802.11ax and 160 MHz: 16 (2.4 GHz) 94 (5 GHz) 110 (2.4 GHz and 5 GHz enabled) Support for IEEE 802.11ax and 80 MHz: 16 (2.4 GHz) 64 (5 GHz) 80 (2.4 GHz and 5 GHz enabled) Support for IEEE 802.11ac: 8 (2.4 GHz) 32 (5 GHz) 40 (2.4 GHz and 5 GHz enabled)
Maximum Number of SSIDs	8
AP Mesh	Yes
Product dimensions (W x D x H)	86mm x 38mm x 86mm (3.39 in. x 1.50 in. x 3.39 in.)

[Download Datasheet](#)

* Harga, spesifikasi, dan ketersediaan bisa berubah dan tidak mengikat

URL : <https://www.citraweb.com/produk/1532/>

Informasi lebih lanjut, pemesanan dan pembelian, hubungi: 0274-554444 atau email sales@citraweb.com