**CITRAWEB SOLUSI TEKNOLOGI**
www.citraweb.com
info@citraweb.com
sales@citraweb.com

# RG-RAP62-Wall-Lite RUIJIE REYEE Wi-Fi 6 AX3000 Dual-Band Wall-Plate AP



**Kode** : RG-RAP62-Wall-Lite
**Brand** : Ruijie - Reyee
**Jenis** : Wireless Indoor
**Harga** : Rp 1.395.000,00

**Ruijie Reyee RG-RAP62-Wall-Lite** AX3000 Wave 2 Dual band (2.4GHz&5GHz) wall-mount access points, 2x2 MU-MIMO, Max. 8 SSID, 2×10/1000Mbps LAN Ports (PoE-In) 803af/at PoE, Max power consumption 11.2 W. Support Beamforming, Layer2/3/AI roaming, WPA2, Router mode, Captive portal, Cloud/Eweb/APP management.

***Belum termasuk adaptor dan poe injector**

***Spesifikasi perangkat dijual bisa berbeda dengan yang ditampilkan karena menyesuaikan dengan regulasi di Indonesia.**

**Produk ini merupakan produk Fix Price. Pembelian produk tidak dapat menggunakan diskon apapun.**

Penawaran Harga Spesial
08112039555

- **Kecepatan Wi-Fi 6 AX3000 maksimal 2401Mbps pada 5 GHz dan maksimal 573 Mbps pada 2.4 GHz**
- **2 x 1GE LAN Port**
- **Ultra-thin design dengan ketebalan 24.8 mm**
- **Kompatibel untuk 86-mm dan EU Standard Junction Boxes**
- **Manajemen terpusat pada Ruijie Cloud**

www.citraweb.com

www.citraweb.com

**Spesifikasi**

| | |
|---|---|
| **Model** | RG-RAP62-Wall-Lite |

**CITRAWEB SOLUSI TEKNOLOGI**
www.citraweb.com
info@citraweb.com
sales@citraweb.com

| | |
|---|---|
| **Wi-Fi Standards** | 2.4GHz<br>Wi-Fi 4 (IEEE 802.11b/g/n)<br>Wi-Fi 6 (IEEE 802.11ax)<br><br>5GHz<br>Wi-Fi 4 (IEEE 802.11a/n)<br>Wi-Fi 5 (IEEE 802.11ac)<br>Wi-Fi 6 (IEEE 802.11ax) |
| **Max. Transmit Power** | 2400–2483.5 MHz, EIRP ≤27 dBm<br>5150–5350 MHz, EIRP ≤23 dBm<br>5725–5825 MHz, EIRP ≤23 dBm |
| **Max Data Rate** | 2.4 GHz: 573 Mbps<br>5 GHz: 2401 Mbps |
| **Spatial Streams** | 2.4 GHz: 2 x 2, MU-MIMO<br>5 GHz: 2 x 2, MU-MIMO |
| **Antennas** | Integrated 2.4 GHz and 5 GHz: 2 built-in omnidirectional antennas |
| **Number of 10/100/1000BASE-T ports** | 2 |
| **Power Supply** | PoE/PoE+ |
| **PoE In standard** | IEEE 802.3af (PoE)<br>IEEE 802.3at (PoE+) |
| **Max. Power Consumption** | 11.2 W |
| **Operating temperature** | 0°C to 40°C (32°F to 104°F) |
| **Storage temperature** | –40°C to +70°C (–40°F to +158°F) |
| **Operating humidity** | 5% RH to 95% RH (non-condensing) |
| **Storage humidity** | 5% RH to 95% RH (non-condensing) |
| **Surge protection** | Ethernet port: ±2 kV for common mode |
| **Mounting options** | Junction box |
| **MTBF** | 400.000 hours |
| **Maximum number of associated wireless clients** | 64 (2.4 GHz)<br>256 (5 GHz)<br>256 (2.4 GHz and 5 GHz enabled) |

www.citraweb.com

| | |
|---|---|
| **Recommended number of clients** | Support for IEEE 802.11ax and 160 MHz:<br>16 (2.4 GHz)<br>94 (5 GHz)<br>110 (2.4 GHz and 5 GHz enabled)<br><br>Support for IEEE 802.11ax and 80 MHz:<br>16 (2.4 GHz)<br>64 (5 GHz)<br>80 (2.4 GHz and 5 GHz enabled)<br><br>Support for IEEE 802.11ac:<br>8 (2.4 GHz)<br>32 (5 GHz)<br>40 (2.4 GHz and 5 GHz enabled) |
| **Maximum Number of SSIDs** | 8 |
| **AP Mesh** | Yes |
| **Product dimensions (W x D x H)** | 86mm x 38mm x 86mm (3.39 in. x 1.50 in. x 3.39 in.) |

**Download Datasheet**

** Harga, spesifikasi, dan ketersediaan bisa berubah dan tidak mengikat*

**URL :** https://www.citraweb.com/produk/1532/

**Informasi lebih lanjut, pemesanan dan pembelian, hubungi: 0274-554444 atau email sales@citraweb.com**

www.citraweb.com