CITRAWEB SOLUSI TEKNOLOGI
www.citraweb.com
info@citraweb.com
sales@citraweb.com

FD1801S-C1 C-DATA 1 PORT COMBO XGS-PON & GPON OLT

Kode : FD1801S-C1
Brand : C-Data
Jenis : FTTH OLT
Harga : Rp 6.810.000,00
~~Rp 7.850.000,00~~

FD1801S-C1 adalah perangkat OLT rack-mounted 1U berstandar ITU-T G.9807.1 yang dilengkapi 2 port Gigabit Ethernet dan 1 port SFP+ 10G uplink port. Pada port PON memiliki COMBO PON (1 XGS-PON & GPON) dengan split ratio 1:128.

***Belum termasuk SFP module.**

Penawaran Harga Spesial
08112039555

Fitur :
- 1*Combo PON port up to 1:128 split ratio.
- Symmetrical 10Gbps transmission rates.
- Uplinks dengan 1 port SFP+ 10G dan 2 port Gigabit Ethernet.
- Jarak transmisi up to 20km.

www.citraweb.com

CITRAWEB SOLUSI TEKNOLOGI
www.citraweb.com
info@citraweb.com
sales@citraweb.com

Spesifikasi

Model	FD1801S-C1
Uplink Port	2* 10/100/1000M auto-negotiation Ethernet ports
	1* SFP+ interfaces
PON Port	Quantity : 1
	Physical interface : SFP slot
	Max splitting ratio : GPON: 1:128
Management Port	1* CONSOLE local management port
Transmission distance	20KM
Port rate	XGS-PON: Downstream: 10Gbps Upstream: 10Gbps GPON: Downstream: 2.5Gbps Upstream: 1.25Gbps
Wavelength	XGS-PON: Forwarding: 1577nm Receiving: 1270nm GPON: Forwarding: 1490nm Receiving: 1310nm
Interface type	SC/UPC
Fiber type	9/125μm SMF (Single Mode Fiber)
Light transmission power	XGS-PON&GPON COMBO 5~8dBm (9.953G) 3~7dBm (2.488G)
Receiving sensitivity	XGS-PON&GPON COMBO ≥-29dBm (9.953G) ≥-30.5dBm (2.488G) ≥-30dBm (1.244G)
Saturation power	XGS-PON&GPON COMBO ≤-8dBm (9.953G) ≤-10dBm (2.488G) ≤-12dBm (1.244G)
Network Management Method	Support CLI, SNMP, TELNET, SSH, WEB
Backplane Bandwidth	44G

www.citraweb.com

Power supply	AC: 100V ~ 240V, 47~63Hz
	DC: External adapter mode 12V/2.5A
	BBU (Backup Battery Unit): DC: 11V?14V. Function: When the regular power supply is cut off, it can be switchedtothebackup power supply, and when the regular power supply resumes, it will switch back to the regular power supply and charge the backuppower supply
Maximum Power	<14W
Working temperature	-15 ~ 50 C
Storage temperature	-40 ~ 85 C
Ambient humidity	5 ~ 90% (Non-condensing)

Download Datasheet

** Harga, spesifikasi, dan ketersediaan bisa berubah dan tidak mengikat*

URL : https://www.citraweb.com/produk/1534/

Informasi lebih lanjut, pemesanan dan pembelian, hubungi: 0274-554444 atau email sales@citraweb.com

www.citraweb.com