CITRAWEB SOLUSI TEKNOLOGI
www.citraweb.com
info@citraweb.com
sales@citraweb.com

TP-LINK EAP225-Outdoor OMADA AC1200 Wireless MU-MIMO Gigabit Indoor/Outdoor Access Point



Kode : EAP225-Outdoor
Brand : TP-Link Omada
Jenis : Wireless Outdoor
Harga : Rp 1.018.000,00

TP-LINK EAP225-Outdoor OMADA merupakan perangkat access point outdoor dengan teknologi **2×2 MIMO** up to 300 Mbps pada 2.4GHz dan 867 Mbps pada 5GHz. Dilengkapi dengan 1 port Gigabit Ethernet (Support 802.3af PoE dan Passive PoE).

Produk ini merupakan produk Fix Price. Pembelian produk tidak dapat menggunakan diskon apapun.

***Spesifikasi perangkat dijual bisa berbeda dengan yang ditampilkan karena menyesuaikan dengan regulasi di Indonesia.**

Penawaran Harga Spesial
08112039555

- **Casing tahan lama dan tahan cuaca untuk aplikasi Wi-Fi luar ruangan.**
- **Kecepatan hingga 1200Mbps dengan teknologi 2×2 MIMO.**
- **Teknologi Omada Mesh memungkinkan konektivitas nirkabel antar AP untuk jangkauan yang lebih luas, sehingga membuat penerapan nirkabel menjadi lebih fleksibel dan nyaman.**
- **Mendukung Seamless Roaming sehingga streaming video dan panggilan suara tidak terpengaruh saat pengguna berpindah antar lokasi.**
- **Antena dengan daya transmisi tinggi dan penguatan tinggi memberikan area cakupan yang luas.**
- **Manajemen terpusat berbasis cloud gratis dan aplikasi Omada untuk kenyamanan dan kemudahan maksimal.**
- **Jaringan tamu yang aman beserta berbagai pilihan otentikasi (SMS/Facebook Wi-Fi/Voucher, dll.) dan teknologi keamanan nirkabel yang melimpah.**
- **Kompatibel dengan 802.3af/Passive PoE (Adaptor PoE disertakan) dan desain pemasangan yang sederhana memungkinkan penerapan yang fleksibel dan instalasi yang mudah.**

www.citraweb.com



Spesifikasi

Model	EAP225-Outdoor
HARDWARE FEATURES	
Interface	Gigabit Ethernet (RJ-45) Port *1 (Support 802.3af PoE and Passive PoE)
Button	Reset
Power Supply	802.3af/A PoE 24V Passive PoE (+4,5pins; -7,8pins. PoE Adapter Included)
Max. Power Consumption	10.5W
Dimensions (W x D x H)	215.7*45*37.7mm (without antenna & mounting kit) 403.8*90.7*55.2mm (with antenna & mounting kit)
Antenna	2.4GHz: 2 * 3dBi 5GHz: 2 * 4dBi
Weatherproof Enclosure	IP65
Mounting	Pole/Wall Mounting (Kits included)
Hardware Watch Dog	Yes
WIRELESS FEATURES	
Concurrent Clients	220+
Wireless Standards	IEEE 802.11a/b/g/n/ac
Frequency	5 GHz and 2.4 GHz

www.citraweb.com

CITRAWEB SOLUSI TEKNOLOGI
www.citraweb.com
info@citraweb.com
sales@citraweb.com

Signal Rate	802.11ac: 5G:6.5 Mbps to 867Mbps(MCS0-MCS9,NSS = 1 to 2 VHT20/40/80) 2.4G:78Mbps to 300Mbps (MCS8-MCS9 VHT20/40, NSS=1 to 3) 802.11n: 6.5 Mbps to 300 Mbps (MCS0-MCS15, VHT 20/40) 802.11g: 6, 9, 12, 18, 24, 36, 48, 54 Mbps 802.11b: 1, 5.5, 11Mbps 802.11a: 6, 9, 12, 18, 24, 36, 48, 54 Mbps
Transmission Power	• CE: <20 dBm (2.4 GHz, EIRP), <27 dBm(5 GHz, EIRP) • FCC: <23 dBm (2.4 GHz), <22 dBm(5 GHz)
Wireless Functions	Multiple SSIDs?Up to 16 SSIDs, 8 for each band? Enable/Disable Wireless Radio Automatic Channel Assignment Transmit Power Control ?Adjust Transmit Power on dBm? QoS(WMM) MU-MIMO Airtime Fairness Beamforming Band Steering Load Balance Rate Limit Reboot Schedule Wireless Schedule Wireless Statistics based on SSID/AP/Client
Wireless Security	Captive Portal Authentication Access Control Wireless Mac Address Filtering Wireless Isolation Between Clients SSID to VLAN Mapping Rogue AP Detection 802.1X Support
Certification	CE, FCC, ROHS
Package Content	Access Point EAP225-Outdoor Passive PoE Adapter Power Cord Mounting Kits Installation Guide Waterproof Ruber Insert Waterproof Antenna
Environment	Operating Temperature: -30C~70C (-22F~158F) Storage Temperature: -40C~70C (-40F~158F) Operating Humidity: 10%~90% non-condensing Storage Humidity: 5%~90% non-condensing

www.citraweb.com

** Harga, spesifikasi, dan ketersediaan bisa berubah dan tidak mengikat*

URL : https://www.citraweb.com/produk/1588/

Informasi lebih lanjut, pemesanan dan pembelian, hubungi: 0274-554444 atau email sales@citraweb.com