CITRAWEB SOLUSI TEKNOLOGI
www.citraweb.com
info@citraweb.com
sales@citraweb.com

TP-LINK ES216G OMADA 16-Port Gigabit Easy Managed Switch



Kode : ES216G
Brand : TP-Link Omada
Jenis : Switch Managed
Harga : Rp 1.137.000,00


TP-LINK ES216G OMADA merupakan switch layer 2 dengan casing Desktop/Rackmount dilengkapi 16 port 10/10/1000 Mbps RJ45, casing metal dan fanless desain.

Produk ini merupakan produk Fix Price. Pembelian produk tidak dapat menggunakan diskon apapun.

Penawaran Harga Spesial
08112039555

- **16 port RJ45 10/100/1000Mbps**
- **Mudah Digunakan: Mendukung plug-and-play untuk konektivitas instan dan konfigurasi sederhana untuk fitur tambahan**
- **Manajemen Cloud Terpusat melalui web atau aplikasi Omada**
- **VLAN, Isolasi Port, Pengujian Kabel, QoS untuk jaringan pengawasan yang andal**
- **Pencegahan Loop Otomatis dan Pengawasan IGMP**
- **Desain tanpa kipas untuk pengoperasian yang senyap**
- **Casing logam yang tahan lama dan desain pemasangan di meja/rak**

www.citraweb.com







www.citraweb.com





Spesifikasi

Model	ES216G
HARDWARE FEATURES	
Interface	• 16× 10/100/1000 Mbps RJ45 Ports • Auto-Negotiation/Auto MDI/MDIX
Fan	Fanless
Physical Security Lock	Yes
Power Supply	100-240 V~50/60 Hz
Dimensions (W x D x H)	11.6 × 5.5 × 1.7 in (294× 140 × 44 mm)
Surge Protection	±6 kV
Mounting	• Desktop • Rackmountable
Max. Power Consumption	8.4 W (110V/60Hz)
Max. Heat Dissipation	28.52 BTU/hr (110 V/60 Hz)
Packet Buffer Memory	4 Mbit
Switching Capacity	32 Gbps

www.citraweb.com

CITRAWEB SOLUSI TEKNOLOGI
www.citraweb.com
info@citraweb.com
sales@citraweb.com

Packet Forwarding Rate	23.8 Mpps
MAC Address Table	8K
Jumbo Frame	15 KB
SOFTWARE FEATURES	
Quality of Service	• Port-based/802.1p/DSCP QoS • 8 Priority Queues • Priority Schedule Mode - WRR (Weighted Round Robin) • Queue Weight Config • Bandwidth Control - Port-Based Rating Limit • Storm Control - Multiple Control Modes (kbps/pps) - Broadcast/Multicast/Unknown-Unicast Control
L2 Features	• Static Link Aggregation • Loop Prevention / Loopback Detection • Flow Control - 802.3x Flow Control • Mirroring - Port Mirroring - One-to-One - Many-to-One - Ingress/Egress/Both • Port Statistics - Port Mirror Status - Traffic Statistics • 802.1ab LLDP
L2 Multicast	• IGMP Snooping - IGMP v1/v2/v3 Snooping - Fast Leave
VLAN	• MTU VLAN • Port-Based VLAN • 802.1Q Tag VLAN - Max 32 VLAN Groups - 4K VID
Transmission Method	Store-And-Forward
OTHERS	
Certification	CE, FCC

www.citraweb.com

Package Content	• ES216G • Power Cord • Rubber Feet • Mounting Brackets • Screws • Installation Guide
Environment	• Operating Temperature: -5–50C (23–122F) • Storage Temperature: -40–70C (-40–158F) • Operating Humidity: 10–90% RH non-condensing • Storage Humidity: 5–90% RH non-condensing

Download Datasheet

** Harga, spesifikasi, dan ketersediaan bisa berubah dan tidak mengikat*

URL : https://www.citraweb.com/produk/1612/

Informasi lebih lanjut, pemesanan dan pembelian, hubungi: 0274-554444 atau email sales@citraweb.com

www.citraweb.com