

# TP-LINK POE10R OMADA Gigabit PoE Splitter



**Kode** : POE10R

**Brand** : TP-Link Omada

**Jenis** : Power Adaptor

**Harga** : Rp 170.000,00

**TP-LINK POE10R OMADA** adalah perangkat Gigabit PoE Splitter kompatibel untuk 802.3af. Keluaran daya yang dapat dipilih 12VDC, 9VDC atau 5VDC.

**Produk ini merupakan produk Fix Price. Pembelian produk tidak dapat menggunakan diskon apapun.**

Penawaran Harga Spesial

 **08112039555**

- Kompatibel dengan IEEE 802.3af
- Keluaran daya yang dapat dipilih
- Dukungan kecepatan Gigabit
- Plug and Play, tidak memerlukan konfigurasi.



#### Spesifikasi

|                                |                                                                                      |
|--------------------------------|--------------------------------------------------------------------------------------|
| <b>Model</b>                   | POE10R                                                                               |
| <b>HARDWARE FEATURES</b>       |                                                                                      |
| <b>Standards and Protocols</b> | IEEE802.3af                                                                          |
| <b>Interface</b>               | 2 10/100/1000Mbps RJ45 Port<br>AUTO Negotiation/AUTO MDI/MDIX<br>1 POWER OUTPUT PORT |

|                                 |                                                                                                                                                                                                                                                                        |
|---------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Network Media</b>            | 10BASE-T: UTP category 3, 4, 5 cable (Max 100m)<br>EIA/TIA-568 100Ω STP (Max 100m)<br>100BASE-TX: UTP category 5, 5e cable (Max 100m)<br>EIA/TIA-568 100Ω STP (Max 100m)<br>1000BASE-T: UTP category 5, 5e, 6 cable (Max 100m)                                         |
| <b>Power Supply</b>             | 12VDC 1A, 9VDC 1A, 5VDC 2A                                                                                                                                                                                                                                             |
| <b>Basic Function</b>           | Compatible With IEEE 802.3af Compliant PSEs<br>Delivers Power Up To 100 Meters<br>Optional 12VDC, 9VDC or 5VDC Power Output                                                                                                                                            |
| <b>LED</b>                      | PWR                                                                                                                                                                                                                                                                    |
| <b>Dimensions ( W x D x H )</b> | 3.2*2.1*0.9 in.(80.8*54*24 mm)                                                                                                                                                                                                                                         |
| <b>Certification</b>            | CE, FCC                                                                                                                                                                                                                                                                |
| <b>Package Content</b>          | <ul style="list-style-type: none"> <li>• POE10R</li> <li>• DC Output Cable</li> <li>• Cat5e Cable</li> <li>• Installation Guide</li> </ul>                                                                                                                             |
| <b>Environment</b>              | <ul style="list-style-type: none"> <li>• Operating Temperature: 0 - 40 °C (32 - 104 °F)</li> <li>• Storage Temperature: -40 - 70 °C (-40 - 158 °F)</li> <li>• Operating Humidity: 10%-90% non-condensing</li> <li>• Storage Humidity: 5%-90% non-condensing</li> </ul> |

[Download Datasheet](#)

\* Harga, spesifikasi, dan ketersediaan bisa berubah dan tidak mengikat

**URL :** <https://www.citraweb.com/produk/1619/>

**Informasi lebih lanjut, pemesanan dan pembelian, hubungi: 0274-554444 atau email [sales@citraweb.com](mailto:sales@citraweb.com)**