# TP-LINK TL-SG1428PE OMADA 28-Port Gigabit Easy Smart Switch with 24-Port PoE+

**Kode** : TL-SG1428PE
**Brand** : TP-Link Omada
**Jenis** : Switch Managed POE
**Harga** : Rp 3.730.000,00

**TP-LINK TL-SG1428PE OMADA** merupakan switch layer 2 dengan casing Rackmount dilengkapi 26 port 10/10/1000 Mbps (24 port support PoE+ up to 250 W) dan 2 port SFP 1G.

**Produk ini merupakan produk Fix Price. Pembelian produk tidak dapat menggunakan diskon apapun.**

Penawaran Harga Spesial
08112039555

- **Switch dengan 24 Port RJ45 PoE+ 10/100/1000Mbps dan 2 Slot SFP**
- **Anggaran daya PoE mencapai 250 W, menjadikannya ideal untuk sistem pengawasan bisnis kecil hingga menengah.**
- **Mode Prioritas membantu menjamin kualitas aplikasi sensitif seperti pemantauan video.**
- **PoE Auto Recovery memungkinkan sistem untuk memperbaiki diri sendiri guna menjamin pengoperasian perangkat yang terhubung melalui PoE secara stabil.**
- **QoS (Quality of Service) bertujuan untuk memberikan pengalaman berselancar internet yang lancar, sedangkan IGMP Snooping mampu mengoptimalkan lalu lintas untuk IPTV.**
- **Manajemen daya cerdas dapat melindungi sakelar dari kelebihan beban.**

www.citraweb.com

BACK VIEW

**Spesifikasi**

| | |
|---|---|
| **Model** | TL-SG1428PE |
| | |
| **HARDWARE FEATURES** | |
| **Interface** | 26x 10/100/1000 Mbps RJ45 Ports<br>2x Gigabit SFP Ports |
| **Fan** | 2 Fans |
| **Physical Security Lock** | Yes |
| **Power Supply** | 100-240V AC, 50/60 Hz |
| **PoE Ports (RJ45)** | Standard: 802.3at/802.3af compliant<br>PoE+ Ports: 24 Ports<br>Power Supply: 250 W |
| **Dimensions ( W x D x H )** | 17.3 × 8.7 × 1.73 in (440 × 220 × 44 mm) |
| **Mounting** | Rackmountable |
| **Max. Power Consumption** | 27 W (220/50Hz. no PD connected)<br>304.7 W (220/50Hz. with 250 W PD connected) |
| **Max. Heat Dissipation** | 92.07 BTU/h (no PD connected)<br>1039.03 BTU/h (with 250 W PD connected) |
| **Packet Buffer Memory** | 4.1Mbit |
| **Switching Capacity** | 56 Gbps |
| **Packet Forwarding Rate** | 41.7 Mpps |
| **MAC Address Table** | 8K |

www.citraweb.com

| | |
|---|---|
| **Jumbo Frame** | 9 KB |
| | |
| **SOFTWARE FEATURES** | |
| **Quality of Service** | Support Port-based 802.1p/DSCP priority<br>Support 4 priority queues<br>Rate Limit<br>Storm Control |
| **L2 Features** | IGMP Snooping V1/V2/V3<br>Static Link Aggregation<br>Port Mirroring<br>Cable Diagnostics<br>Loop Prevention<br>PoE Auto Recovery |
| **VLAN** | Supports up to 32 VLANs simultaneously (out of 4K VLAN IDs)<br>MTU/Port/Tag VLAN |
| **Transmission Method** | Store-And-Forward |
| | |
| **OTHERS** | |
| **Certification** | CE, FCC |
| **Package Content** | TL-SG1428PE<br>Power Cord<br>Installation Guide<br>Rackmount Kit<br>Rubber Feet |
| **Environment** | • Operating Temperature: 0~50C (32~122F)<br>• Storage Temperature: -40–70C (-40–158F)<br>• Operating Humidity: 10–90% RH non-condensing<br>• Storage Humidity: 5–90% RH non-condensing |

www.citraweb.com

**Download Datasheet**

** Harga, spesifikasi, dan ketersediaan bisa berubah dan tidak mengikat*

**URL :** https://www.citraweb.com/produk/1669/

**Informasi lebih lanjut, pemesanan dan pembelian, hubungi: 0274-554444 atau email sales@citraweb.com**