

TP-LINK TL-SG1218MP OMADA 18-Port Gigabit Rackmount Unmanaged Switch with 16 PoE+

Kode : TL-SG1218MP

Brand : TP-Link Omada

Jenis : Switch Unmanaged POE

Harga : Rp 2.823.000,00



TP-LINK TL-SG1218MP OMADA merupakan unmanaged switch yang dilengkapi 16 port Gigabit PoE+, 2 port Gigabit non-PoE dan 2 port Combo Gigabit SFP. Menggunakan standard IEEE 802.3af/at yang mampu memberikan daya PoE hingga 250W (maksimal 30W pada setiap port).

Produk ini merupakan produk Fix Price. Pembelian produk tidak dapat menggunakan diskon apapun.

Penawaran Harga Spesial

 **08112039555**

- 16 port RJ45 PoE+ gigabit, 2 port RJ45 non-PoE gigabit, dan 2 slot SFP gigabit kombo
- Anggaran daya PoE tinggi hingga 30 W untuk setiap port PoE dan 250 W untuk semua port PoE
- Bekerja dengan PD yang sesuai dengan standar IEEE 802.3af/at
- Plug-and-Play, tanpa perlu konfigurasi dan instalasi
- QoS 802.1p/DSCP memungkinkan kelancaran lalu lintas yang sensitif terhadap latensi.
- Casing logam yang tahan lama dan desain pembuangan panas profesional memastikan rentang suhu operasi yang luas (0-50C).

BACK VIEW

Spesifikasi

Model	TL-SG1218MP
HARDWARE FEATURES	
Interface	• 16 port RJ45 gigabit PoE+ • 2 port RJ45 gigabit non-PoE • 2 slot SFP gigabit combo
Fan	2
Physical Security Lock	Yes
Power Supply	100-240 VAC, 50/60 Hz
PoE Ports (RJ45)	• Standard: 802.3at/802.3af compliant • PoE Ports: Ports 1-16 • PoE Power Budget: 250 W
Dimensions (W x D x H)	17.3 x 7.1 x 1.73 in (440 x 180 x 44 mm)
Mounting	Rack Mountable
Max. Power Consumption	• 21.4 W (220/50 Hz. no PD connected) • 286.64 W (220/50 Hz. with 250 W PD connected)
Max. Heat Dissipation	• 72.97 BTU/h (no PD connected) • 977.44 BTU/h (with 250 W PD connected)
Packet Buffer Memory	4.1 Mbit
Jumbo Frame	10 KB

Switching Capacity	36 Gbps
Packet Forwarding Rate	26.78 Mbps
MAC Address Table	8K
Advanced Features	• Compatible With IEEE 802.3af/at Compliant PDs • 802.1p/DHCP QoS • Mac Address Auto-Learning And Auto-Aging • IEEE802.3x Flow Control For Full-Duplex Mode And Backpressure For Half-Duplex Mode
OTHERS	
Certification	CE, FCC
Package Content	• TL-SG1218MP • Installation Guide • Power Cord • Rackmount Kit • Rubber Feet
Environment	• Operating Temperature: 0-50 C (32-122 F) • Storage Temperature: -40-70 C (-40-158 F) • Operating Humidity: 10-90% RH non-condensing • Storage Humidity: 5-90% RH non-condensing

[Download Datasheet](#)

* Harga, spesifikasi, dan ketersediaan bisa berubah dan tidak mengikat

URL : <https://www.citraweb.com/produk/1686/>

Informasi lebih lanjut, pemesanan dan pembelian, hubungi: 0274-554444 atau email sales@citraweb.com