

TP-LINK TL-SL1226P OMADA 24-Port 10/100Mbps PoE+ 2-Port Gigabit Unmanaged Switch

Kode : TL-SL1226P
Brand : TP-Link Omada
Jenis : Switch Unmanaged POE
Harga : Rp 2.799.000,00



TP-LINK TL-SL1226P OMADA merupakan unmanaged switch yang dilengkapi 24 port PoE+ 10/100 Mbps RJ45, 2 port Gigabit dan 2 port Combo Gigabit SFP. Switch ini mampu memberikan daya PoE hingga 250W.

Produk ini merupakan produk Fix Price. Pembelian produk tidak dapat menggunakan diskon apapun.

Penawaran Harga Spesial
 **08112039555**

- 24 port PoE+ 10/100 Mbps RJ45, 2 port Gigabit RJ45, dan 2 slot combo Gigabit SFP.
- Anggaran daya PoE tinggi hingga 30 W untuk setiap port PoE dan 250 W untuk semua port PoE.
- Mode Prioritas memastikan prioritas tinggi pada port 1-8 untuk menjamin kualitas aplikasi sensitif seperti monitor video.
- Mode Isolasi memungkinkan pemisahan lalu lintas klien dengan sekali klik untuk keamanan dan kinerja yang lebih tinggi.
- Pasang dan mainkan, tanpa perlu konfigurasi dan instalasi.

Spesifikasi

Model	TL-SL1226P
HARDWARE FEATURES	
Interface	• 24× PoE+ 10/100 Mbps RJ45 Ports • 2× 10/100/1000 Mbps RJ45 Ports • 2× Combo Gigabit SFP Slots
Fan	2 Fans
Physical Security Lock	Yes
Power Supply	100-240 VAC, 50/60 Hz

PoE Ports (RJ45)	• Standard: 802.3 af/at compliant • PoE Ports: Ports 1-24 • Power Supply: 250 W
Dimensions (W x D x H)	17.3 x 7.1 x 1.7 in (440 x 180 x 44 mm)
Max. Power Consumption	14.81 W (220/50 Hz. no PD connected) 302.88 W (220/50 Hz. with 250 W PD connected)
Max. Heat Dissipation	50.35 BTU/h (no PD connected) 1029.79 BTU/h (with 250 W PD connected)
Jumbo Frame	10 KB
Switching Capacity	8.8 Gbps
Packet Forwarding Rate	6.54 Mpps
MAC Address Table	8K
Advanced Features	Compatible With IEEE 802.3at/af Compliant PDs Extend Mode (Up to 250m PoE power supply and data transmission) Priority Mode (Ports 1-8) Isolation Mode (Ports 1-24) PoE Auto Recovery (Ports 1-24) PD Detection Intelligent Power Supply Mac Address Auto-Learning and Auto-Aging IEEE802.3x Flow Control
OTHERS	
Certification	CE, FCC
Package Content	TL-SL1226P Power Cable Installation Guide Two mounting brackets and the fittings
Environment	• Operating Temperature: 0-50 C (32-122 F) • Storage Temperature: -40-70 C (-40-158 F) • Operating Humidity: 10-90% RH non-condensing • Storage Humidity: 5-90% RH non-condensing

[Download Datasheet](#)

* Harga, spesifikasi, dan ketersediaan bisa berubah dan tidak mengikat

URL : <https://www.citraweb.com/produk/1695/>

Informasi lebih lanjut, pemesanan dan pembelian, hubungi: 0274-554444 atau email sales@citraweb.com