

TP-LINK TL-SF1009P OMADA 9-Port 10/100Mbps Desktop Unmanaged Switch with 8-Port PoE+

Kode : TL-SF1009P**Brand** : TP-Link Omada**Jenis** : Switch Unmanaged POE**Harga** : Rp 586.000,00

TP-LINK TL-SF1009P OMADA merupakan unmanaged switch yang dilengkapi 9 Port 10/100 Mbps RJ45 (8 Port support 802.3af/at PoE+). Switch ini mampu memberikan daya PoE hingga 65W.

Produk ini merupakan produk Fix Price. Pembelian produk tidak dapat menggunakan diskon apapun.

Penawaran Harga Spesial **08112039555**

- 9 port RJ45 10/100 Mbps
- 8 port PoE+ mentransfer data dan daya melalui kabel terpisah.
- Kompatibel dengan PD yang sesuai dengan standar IEEE 802.3af/at.
- Mendukung daya PoE hingga 30 W untuk setiap port PoE.
- Mendukung daya PoE hingga 65 W untuk 8 port PoE.
- Mode Prioritas memastikan prioritas tinggi pada port 1-2 untuk menjamin kualitas aplikasi sensitif.
- Mode Isolasi memungkinkan pemisahan lalu lintas klien dengan sekali klik untuk keamanan dan kinerja yang lebih tinggi.
- Pasang dan mainkan, tanpa perlu konfigurasi dan instalasi.

Spesifikasi

Model	TL-SF1009P
HARDWARE FEATURES	
Interface	• 9× 10/100 Mbps RJ45 Ports (8× 10/100 Mbps 802.3af/at PoE+ ports) • AUTO Negotiation • AUTO MDI/MDIX
Fan	Fanless
Physical Security Lock	Yes
Power Supply	External Power Adapter (Output: 53.5VDC / 1.31A)

PoE Ports (RJ45)	• Standard: 802.3 af/at compliant • PoE Ports: Ports 1-8 • Power Supply: 65 W
Dimensions (W x D x H)	6.7 x 3.9 x 1.1 in (171 x 98 x 27 mm)
Max. Power Consumption	• 3.6 W (220/50 Hz. no PD connected) • 77.08 W (220/50 Hz. with 65 W PD connected)
Max. Heat Dissipation	• 12.28 BTU/h (no PD connected) • 262.84 BTU/h (with 65 W PD connected)
Jumbo Frame	2 KB
Switching Capacity	1.8 Gbps
Packet Forwarding Rate	1.3392 Mpps
MAC Address Table	2K
Advanced Features	• Compatible With IEEE 802.3af/at Compliant PDs • Extend Mode Button (Ports 1-4 and Ports 1-8, Up to 250 m PoE power supply and data transmission) • Priority Mode Button (Ports 1-2) • Isolation Mode Button (Ports 1-8) • Mac Address Auto-Learning and Auto-Aging • IEEE802.3x Flow Control For Full-Duplex Mode And Backpressure for Half-Duplex Mode
OTHERS	
Certification	CE, FCC
Package Content	• TL-SF1009P • Power Adapter • Installation Guide
Environment	• Operating Temperature: 0-40 C (32-104 F) • Storage Temperature: -40-70 C (-40-158 F) • Operating Humidity: 10-90% RH non-condensing • Storage Humidity: 5-90% RH non-condensing

[Download Datasheet](#)

* Harga, spesifikasi, dan ketersediaan bisa berubah dan tidak mengikat

URL : <https://www.citraweb.com/produk/1701/>

Informasi lebih lanjut, pemesanan dan pembelian, hubungi: 0274-554444 atau email sales@citraweb.com