TP-LINK TL-SF1008LP OMADA 8-Port 10/100Mbps Desktop Unmanaged Switch with 4-Port PoE

Kode : TL-SF1008LP
Brand : TP-Link Omada
Jenis : Switch Unmanaged POE
Harga : Rp 514.000,00

TP-LINK TL-SF1008LP OMADA merupakan unmanaged switch yang dilengkapi 8 Port 10/100 Mbps RJ45 (4 Port support 802.3af PoE). Switch ini mampu memberikan daya PoE hingga 41W.

Produk ini merupakan produk Fix Price. Pembelian produk tidak dapat menggunakan diskon apapun.

Penawaran Harga Spesial
08112039555

- **8 port RJ45 10/100 Mbps**
- **4 port PoE mentransfer data dan daya melalui kabel terpisah.**
- **Kompatibel dengan PD yang sesuai dengan standar IEEE 802.3af.**
- **Mode Prioritas memastikan prioritas tinggi pada port 1–2 untuk menjamin kualitas aplikasi sensitif.**
- **Mendukung daya PoE hingga 41 W untuk semua port PoE.**
- **Plug-and-Play, tanpa perlu konfigurasi dan instalasi.**

Spesifikasi

Model	TL-SF1008LP
HARDWARE FEATURES	
Interface	• 8× 10/100 Mbps RJ45 Ports (Ports 1–4 support 802.3af PoE) • AUTO Negotiation • AUTO MDI/MDIX
Fan	Fanless
Physical Security Lock	Yes
Power Supply	External Power Adapter (Output: 53.5 V DC / 0.81 A)

www.citraweb.com

PoE Ports (RJ45)	• Standard: 802.3 af compliant • PoE Ports: Ports 1–4 • Power Supply: 41 W
Dimensions (W x D x H)	6.7 × 3.9 × 1.1 in (171 × 98 × 27 mm)
Max. Power Consumption	• 2.2 W (220 V/ 50 Hz. no PD connected) • 47.1 W (220 V/ 50 Hz. with 41 W PD connected)
Max. Heat Dissipation	• 7.5 BTU/h(no PD connected) • 160.61 BTU/h(with 41 W PD connected)
Jumbo Frame	2 KB
Switching Capacity	1.6 Gbps
Packet Forwarding Rate	1.1904 Mpps
MAC Address Table	2K
Advanced Features	• Compatible With IEEE 802.3af Compliant PDs • Extend Mode Button (Ports 1–4) • Priority Mode Button (Ports 1–2) • Mac Address Auto-Learning and Auto-Aging • IEEE802.3x Flow Control for Full-Duplex Mode and Backpressure for Half-Duplex Mode
OTHERS	
Certification	CE, FCC
Package Content	• TL-SF1008LP • Power Adapter • Installation Guide
Environment	• Operating Temperature: 0–40 C (32–104 F) • Storage Temperature: -40–70 C (-40–158 F) • Operating Humidity: 10–90% RH non-condensing • Storage Humidity: 5–90% RH non-condensing

www.citraweb.com

Download Datasheet

** Harga, spesifikasi, dan ketersediaan bisa berubah dan tidak mengikat*

URL : https://www.citraweb.com/produk/1703/

Informasi lebih lanjut, pemesanan dan pembelian, hubungi: 0274-554444 atau email sales@citraweb.com