TP-LINK TL-SF1006P OMADA 6-Port 10/100Mbps Desktop Unmanaged Switch with 4-Port PoE+

Kode : TL-SF1006P
Brand : TP-Link Omada
Jenis : Switch Unmanaged POE
Harga : Rp 514.000,00

TP-LINK TL-SF1006P OMADA merupakan unmanaged switch yang dilengkapi 6 Port 10/100 Mbps RJ45 (4 Port support 802.3af/at PoE+). Switch ini mampu memberikan daya PoE hingga 67W.

Produk ini merupakan produk Fix Price. Pembelian produk tidak dapat menggunakan diskon apapun.

Penawaran Harga Spesial
08112039555

- **6 port RJ45 10/100 Mbps.**
- **4 port PoE+ mentransfer data dan daya melalui kabel terpisah.**
- **Kompatibel dengan PD yang sesuai dengan standar IEEE 802.3af/at.**
- **Mode Prioritas memastikan prioritas tinggi pada port 1–2 untuk menjamin kualitas aplikasi sensitif.**
- **PoE Auto Recovery menjamin pengoperasian perangkat PoE yang stabil dengan secara otomatis melakukan reboot perangkat PD yang terputus atau tidak responsif.**
- **Mendukung daya PoE hingga 30 W untuk setiap port PoE.**
- **Mendukung daya PoE hingga 67 W untuk semua port PoE**
- **Plug-and-Play, tanpa perlu konfigurasi dan instalasi.**

Spesifikasi

Model	TL-SF1006P
HARDWARE FEATURES	
Interface	• 6× 10/100 Mbps RJ45 Ports (ports 1–4 support 802.3af/at PoE+) • AUTO Negotiation • AUTO MDI/MDIX
Fan	Fanless
Physical Security Lock	Yes
Power Supply	External Power Adapter (Output: 53.5VDC / 1.31A)

www.citraweb.com

PoE Ports (RJ45)	• Standard: 802.3 af/at compliant • PoE Ports: Ports 1–4 • Power Supply: 67 W
Dimensions (W x D x H)	6.2 x 4.0 x 1.0 in (158 x 101 x 25 mm)
Max. Power Consumption	• 2.52 W (220 V / 50 Hz, no PD connected) • 75.4 W (220 V / 50 Hz, with 67 W PD connected)
Max. Heat Dissipation	• 8.59 BTU/h(no PD connected) • 257.11 BTU/h(with 67 W PD connected)
Jumbo Frame	2 KB
Switching Capacity	1.2 Gbps
Packet Forwarding Rate	0.8928 Mpps
MAC Address Table	2K
Advanced Features	• Compatible With IEEE 802.3af/at Compliant PDs • Extend Mode Button (Ports 1–4) • Priority Mode Button (Ports 1–2) • PoE Auto Recovery (Ports 1-4) • Mac Address Auto-Learning and Auto-Aging • IEEE802.3x Flow Control For Full-Duplex Mode and Backpressure for Half-Duplex Mode
OTHERS	
Certification	CE, FCC
Package Content	• TL-SF1006P • Power Adapter • Installation Guide
Environment	• Operating Temperature: 0–40 C (32–104 F) • Storage Temperature: -40–70 C (-40–158 F) • Operating Humidity: 10–90% RH non-condensing • Storage Humidity: 5–90% RH non-condensing

www.citraweb.com

Download Datasheet

** Harga, spesifikasi, dan ketersediaan bisa berubah dan tidak mengikat*

URL : https://www.citraweb.com/produk/1704/

Informasi lebih lanjut, pemesanan dan pembelian, hubungi: 0274-554444 atau email sales@citraweb.com