

# TP-LINK TL-SF1005P OMADA 6-Port 10/100Mbps Desktop Unmanaged Switch with 4-Port PoE+

**Kode** : TL-SF1005P**Brand** : TP-Link Omada**Jenis** : Switch Unmanaged POE**Harga** : Rp 452.000,00

**TP-LINK TL-SF1005P OMADA** merupakan unmanaged switch yang dilengkapi 5 Port 10/100 Mbps RJ45 (4 Port support 802.3af/at PoE+). Switch ini mampu memberikan daya PoE hingga 67W.

**Produk ini merupakan produk Fix Price. Pembelian produk tidak dapat menggunakan diskon apapun.**

**Penawaran Harga Spesial** **08112039555**

- 5 port RJ45 10/100 Mbps.
- 4 port PoE+ mentransfer data dan daya melalui kabel terpisah.
- Kompatibel dengan PD yang sesuai dengan standar IEEE 802.3af/at.
- Mendukung daya PoE hingga 30 W untuk setiap port PoE.
- Mendukung daya PoE hingga 67 W untuk semua port PoE.
- Mode Prioritas memastikan prioritas tinggi pada port 1-2 untuk menjamin kualitas aplikasi yang sensitif.
- PoE Auto Recovery menjamin pengoperasian perangkat PoE yang stabil dengan secara otomatis melakukan reboot perangkat PD yang terputus atau tidak responsif.
- Plug-and-Play, tanpa perlu konfigurasi dan instalasi.

**BACK VIEW**

**Spesifikasi**

|                                 |                                                                                                                                                                             |
|---------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Model</b>                    | TL-SF1005P                                                                                                                                                                  |
| <b>HARDWARE FEATURES</b>        |                                                                                                                                                                             |
| <b>Interface</b>                | <ul style="list-style-type: none"> <li>• 5 × 10/100 Mbps RJ45 Ports (4 × 10/100 Mbps 802.3af/at PoE+ ports)</li> <li>• AUTO Negotiation</li> <li>• AUTO MDI/MDIX</li> </ul> |
| <b>Fan</b>                      | Fanless                                                                                                                                                                     |
| <b>Physical Security Lock</b>   | Yes                                                                                                                                                                         |
| <b>Power Supply</b>             | External Power Adapter (Output: 53.5VDC / 1.31A)                                                                                                                            |
| <b>PoE Ports (RJ45)</b>         | <ul style="list-style-type: none"> <li>• Standard: 802.3 af/at compliant</li> <li>• PoE Ports: Ports 1-4</li> <li>• Power Supply: 67 W</li> </ul>                           |
| <b>Dimensions ( W x D x H )</b> | 3.9 x 3.9 x 1.0 in (99.8 x 98 x 25 mm)                                                                                                                                      |
| <b>Max. Power Consumption</b>   | <ul style="list-style-type: none"> <li>• 1.9 W (220 V / 50 Hz, no PD connected)</li> <li>• 74 W (220 V / 50 Hz, with 67 W PD connected)</li> </ul>                          |
| <b>Max. Heat Dissipation</b>    | <ul style="list-style-type: none"> <li>• 6.48 BTU/h(no PD connected)</li> <li>• 252.34 BTU/h(with 67 W PD connected)</li> </ul>                                             |
| <b>Jumbo Frame</b>              | 2 KB                                                                                                                                                                        |
| <b>Switching Capacity</b>       | 1 Gbps                                                                                                                                                                      |
| <b>Packet Forwarding Rate</b>   | 0.744 Mpps                                                                                                                                                                  |

|                          |                                                                                                                                                                                                                                                                                                                                           |
|--------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>MAC Address Table</b> | 2K                                                                                                                                                                                                                                                                                                                                        |
| <b>Advanced Features</b> | <ul style="list-style-type: none"> <li>• Compatible With IEEE 802.3af/at Compliant PDs</li> <li>• Extend Mode Button (Ports 1-4)</li> <li>• Priority Mode Button (Ports 1-2)</li> <li>• Mac Address Auto-Learning And Auto-Aging</li> <li>• IEEE802.3x Flow Control For Full-Duplex Mode And Backpressure For Half-Duplex Mode</li> </ul> |
| <b>OTHERS</b>            |                                                                                                                                                                                                                                                                                                                                           |
| <b>Certification</b>     | CE, FCC                                                                                                                                                                                                                                                                                                                                   |
| <b>Package Content</b>   | <ul style="list-style-type: none"> <li>• TL-SF1005P</li> <li>• Power Adapter</li> <li>• Installation Guide</li> </ul>                                                                                                                                                                                                                     |
| <b>Environment</b>       | <ul style="list-style-type: none"> <li>• Operating Temperature: 0-40 C (32-104 F)</li> <li>• Storage Temperature: -40-70 C (-40-158 F)</li> <li>• Operating Humidity: 10-90% RH non-condensing</li> <li>• Storage Humidity: 5-90% RH non-condensing</li> </ul>                                                                            |

[Download Datasheet](#)

\* Harga, spesifikasi, dan ketersediaan bisa berubah dan tidak mengikat

**URL :** <https://www.citraweb.com/produk/1705/>

**Informasi lebih lanjut, pemesanan dan pembelian, hubungi: 0274-554444 atau email [sales@citraweb.com](mailto:sales@citraweb.com)**