TP-LINK LS109P OMADA 9-Port 10/100Mbps Desktop Unmanaged Switch with 8-Port PoE+

Kode : LS109P
Brand : TP-Link Omada
Jenis : Switch Unmanaged POE
Harga : Rp 470.000,00

TP-LINK LS109P OMADA merupakan unmanaged switch LiteWave series yang dilengkapi 9 port 10/100 Mbps RJ45 auto-negotiation (Port 1-8 support PoE+ output maksimal 63W) menyediakan kapasitas switching hingga 1.8 Gbps.

Produk ini merupakan produk Fix Price. Pembelian produk tidak dapat menggunakan diskon apapun.

Penawaran Harga Spesial
08112039555

- **Anggaran PoE 63 W** : Delapan port PoE 10/100 Mbps yang sesuai dengan standar 802.3af/at dengan mudah menghubungkan dan memberi daya pada perangkat tetap seperti kamera IP, titik akses, dan telepon IP melalui satu kabel. Setiap port PoE mendukung output PoE hingga 30 W.
- **Transmisi PoE hingga 250 m** : Dengan Mode Perluasan, jarak transmisi PoE mencapai hingga 250m, sangat cocok untuk pemasangan kamera pengawasan di area yang luas.
- **PoE Auto Recovery** : Secara otomatis memulai ulang perangkat bertenaga PoE Anda yang terjatuh atau tidak responsif.
- **Pemisahan Lalu Lintas untuk Keamanan Lebih Tinggi** : Mode Isolasi memungkinkan pemisahan lalu lintas klien dengan sekali klik untuk menghindari pengintipan dan perusakan, serta mengisolasi badai siaran.
- **Plug and Play** : Cukup colokkan dan mainkan untuk konektivitas instan tanpa perlu konfigurasi.
- **Pengoperasian Senyap** : Desain tanpa kipas mengurangi konsumsi daya dan memastikan pengoperasian yang senyap, ideal untuk rumah atau bisnis yang sensitif terhadap kebisingan.
- **Desain Perangkat Keras yang Andal** : Casing logam yang tahan lama dan desain pemasangan di meja/dinding sangat cocok untuk berbagai lingkungan.

www.citraweb.com

BACK VIEW

Spesifikasi

Model	LS109P
HARDWARE FEATURES	
Interface	• 9× 10/100 Mbps RJ45 Ports (8× 10/100 Mbps 802.3af/at PoE+ Ports) • AUTO Negotiation • AUTO MDI/MDIX
Fan	Fanless
Physical Security Lock	Yes
Power Supply	External Power Adapter(Output: 53.5VDC / 1.31A)
PoE Ports (RJ45)	• Standard: 802.3 af/at compliant • PoE Ports: Ports 1–8, up to 30 W PoE output per port • Power Supply: 63 W
Dimensions (W x D x H)	6.7×3.9×1.1 in (171×98×27 mm)
Max. Power Consumption	• 3.67 W (220 V/50 Hz no PD connected) • 73.24 W (220 V/50 Hz with 63 W PD connected)
Max. Heat Dissipation	• 12.48 BTU/h (220 V/50 Hz no PD connected) • 249 BTU/h (220 V/50 Hz with 63 W PD connected)
Jumbo Frame	1.5 KB
Switching Capacity	1.8 Gbps
Packet Forwarding Rate	1.3392 Mpps

www.citraweb.com

MAC Address Table	2K
Advanced Features	• Extend Mode Button (Ports 1–4/1–8, Up to 250 m PoE power supply and data transmission) • Isolation Mode Button (Ports 1–8) • PoE Auto Recovery Button (Ports 1–8) • Compatible With IEEE 802.3af/at Compliant PDs • Mac Address Auto-Learning and Auto-Aging • IEEE 802.3x Flow Control • Green Technology
OTHERS	
Certification	CE, FCC
Package Content	• LS109P • Power Adapter • Installation Guide • Rubber Feet
Environment	• Operating Temperature: 0–40 C (32–104 F) • Storage Temperature: -40–70 C (-40–158 F) • Operating Humidity: 10–90% RH non-condensing • Storage Humidity: 5–90% RH non-condensing

Download Datasheet

** Harga, spesifikasi, dan ketersediaan bisa berubah dan tidak mengikat*

URL : https://www.citraweb.com/produk/1708/

Informasi lebih lanjut, pemesanan dan pembelian, hubungi: 0274-554444 atau email sales@citraweb.com

www.citraweb.com