TP-LINK LS105GP OMADA 5-Port Gigabit Desktop Unmanaged Switch with 4-Port PoE+

Kode : LS105GP
Brand : TP-Link Omada
Jenis : Switch Unmanaged POE
Harga : Rp 418.000,00

TP-LINK LS105GP OMADA merupakan unmanaged switch LiteWave series yang dilengkapi 5 port 10/100/1000Mbps RJ45 auto-negotiation (Port 1-4 support PoE+ output maksimal 65W) menyediakan kapasitas switching hingga 10 Gbps.

Produk ini merupakan produk Fix Price. Pembelian produk tidak dapat menggunakan diskon apapun.

Penawaran Harga Spesial
08112039555

- **Port Gigabit Penuh** : Lima port negosiasi otomatis gigabit menyediakan kapasitas switching hingga 10 Gbps.
- **Anggaran PoE 65 W** : Empat port PoE+ gigabit yang sesuai dengan standar 802.3af/at dengan mudah menghubungkan dan memberi daya pada perangkat tetap seperti kamera IP, titik akses, dan telepon IP melalui satu kabel. Output PoE hingga 30 W didukung oleh setiap port PoE.
- **Transmisi PoE hingga 250 m** : Dengan Mode Perluasan, jarak transmisi PoE mencapai hingga 250m, sangat cocok untuk pemasangan kamera pengawasan di area yang luas.
- **PoE Auto Recovery** : Secara otomatis memulai ulang perangkat bertenaga PoE Anda yang terjatuh atau tidak responsif.
- **Plug and Play** : Cukup colokkan dan mainkan untuk konektivitas instan tanpa perlu konfigurasi.
- **Pengoperasian Senyap** : Desain tanpa kipas mengurangi konsumsi daya dan memastikan pengoperasian yang senyap, ideal untuk rumah atau bisnis yang sensitif terhadap kebisingan.
- **Desain Perangkat Keras yang Andal** : Casing logam yang tahan lama dan desain pemasangan di meja/dinding sangat cocok untuk berbagai lingkungan.

www.citraweb.com

Spesifikasi

Model	LS105GP
HARDWARE FEATURES	
Interface	• 5× 10/100/1000Mbps RJ45 Ports (Ports 1–4 supports 802.3af/at PoE+) • AUTO Negotiation • AUTO MDI/MDIX
Fan	Fanless
Power Supply	External Power Adapter (Output: 53.5 VDC / 1.31 A)

PoE Ports (RJ45)	• Standard: 802.3 af/at compliant • PoE Ports: Ports 1–4, up to 30 W PoE output per port • Power Supply: 65 W
Dimensions (W x D x H)	3.9×3.9×1.0 in (99.8×98×25 mm)
Max. Power Consumption	• 4 W (220/50 Hz. no PD connected) • 74.46 W (220/50 Hz. with 65 W PD connected)
Max. Heat Dissipation	• 13.6 BTU/h (no PD connected) • 253.16 BTU/h (with 65 W PD connected)
Jumbo Frame	16 KB
Switching Capacity	10 Gbps
Packet Forwarding Rate	7.44 Mpps
MAC Address Table	2K
Advanced Features	• Extend Mode Button (Ports 1–2, Up to 250 m PoE power supply and data transmission) • PoE Auto Recovery Button (Ports 1-4) • Compatible With IEEE 802.3af/at Compliant PDs • Mac Address Auto-Learning and Auto-Aging • IEEE 802.3x Flow Control • 802.1p/DSCP QoS • IGMP Snooping • Green Technology
OTHERS	
Certification	CE, FCC
Package Content	• LS105GP • Power Adapter • Installation Guide
Environment	• Operating Temperature: 0–40 C (32–104 F) • Storage Temperature: -40–70 C (-40–158 F) • Operating Humidity: 10–90% RH non-condensing • Storage Humidity: 5–90% RH non-condensing

www.citraweb.com

Download Datasheet

** Harga, spesifikasi, dan ketersediaan bisa berubah dan tidak mengikat*

URL : https://www.citraweb.com/produk/1711/

Informasi lebih lanjut, pemesanan dan pembelian, hubungi: 0274-554444 atau email sales@citraweb.com