

On Line UPS PlusIII-3KLRB



Kode : PlusIII-3KLRB

Kategori : Discontinued

Harga : Rp 10.585.000,00

PlusIII-3KLRB adalah produk dari APlus UPS System dengan rating 3000VA/2700Watt dan memiliki desain ganda (tower / rackmount) serta kemampuan "Easy Battery Replacement".

Dilengkapi dengan External Battery Bank dan juga memungkinkan untuk di tambah lagi dengan beberapa External Battery Bank. Dilengkapi dengan external PDU dan sekaligus MBS (Maintenance Bypass Switch) sehingga memungkinkan pengguna untuk mudah melakukan maintenance atau mengganti battery jika sudah lemah.

***Penjualan produk ini tidak termasuk battery**

Features :

- High performance true double conversion On Line UPS 3000VA
- Individual power distribution unit (PDU) maintenance bypass switch
- Intelligent Card (SNMP) Included + USB multiple communications
- External battery bank to extend back-up time (Optional)
- Microprocessor control guarantees high reliability
- Low heat dissipation in long time operation
- Emergency power-off function (EPO)
- Automatic self-testing function
- High efficiency mode (ECO mode)
- Output voltage regulation < 2%
- Power management software
- Output power factor 0.9
- Wide input range
- Fan speed control
- DC start

Battery Type :

- VRLA 12V/9AH or VRLA 12V/7.2AH
- 8 pcs
- **Battery dimension 151 x 65 x 100 mm**

Backup Time (estimated for 1 battery bank installed) :

| LOAD | 9AH Battery | 7.2AH Battery |
|-----------|-------------|---------------|
| 2200 Watt | 16 Minutes | 13 Minutes |
| 1300 Watt | 27 Minutes | 22 Minutes |
| 900 Watt | 40 Minutes | 32 Minutes |

External Battery Bank :

BBR2B-96V

- 1 unit battery bank already included in the package
- 2 unit additional battery bank possible to install
- maximum total of 3 battery bank installed

Easy Maintenance and Installation :





Manual :

[UPS-Aplus-PlusIII-HV.pdf](#)

Battery Installation guide :

[APlus_Battery_Box-BBR2B_96V-Instalation_Guide](#)

Add-on Accessories :

[Universal Rackmount L Rail](#)

Specification :

| | |
|--------------------------|--|
| INPUT | |
| Voltage | 1 Phase 2 Wires with Ground 220/230/240Vac |
| Voltage Range | 110-300Vac |
| Frequency | 50Hz or 60Hz (Auto-Sensing) |
| THDi | < 5% at full Load |
| OUTPUT | |
| Voltage | 220/230/240Vac |
| Voltage Range | +/- 2% |
| Frequency (Battery Mode) | 50Hz or 60Hz +/- 0.2Hz |
| Waveform | Pure Sinewave |
| THD | < 3%(linear load), < 5%(non-linear load) |
| Crest Ratio | 3:1 |
| EFFICIENCY | |
| To AC Mode | > 88% |
| To Battery Mode | > 85% |
| To ECO Mode | > 93% |
| BATTERY | |
| Voltage | 96VDC |

| | |
|------------------------------|---|
| Type | 12V/7AH*8pcs |
| Recharge Time | 5 hours to 90% |
| TRANSFER TIME | |
| Line Mode to Battery Mode | 0ms |
| Inverter to Bypass, ECO Mode | < 4ms |
| ECO Mode to Inverter | < 10ms |
| DISPLAY | |
| LCD Display | Input, Output, Load, Battery, Mode/Fault/Warning code, Inverter operating, Bypass operating, Output voltage and frequency and Bypass disable / enable selection information |
| AUDIBLE ALARM | |
| Battery Mode | Beeps Every 4 Seconds |
| Low Battery | Sounding Every Second |
| Overload | Sounding Twice Every Second |
| Fault | Beeping continuously |
| COMMUNICATIONS | |
| Interface (Port) | USB Port |
| Intelligent Slot | Slot for SNMP or AS400 card (Optional) |
| EPO | Emergency Power Off |
| ENVIRONMENT | |
| Operating Temperature | 0° C - 45° C |
| Humidity | 20-90% (Non-condensing) |
| Acoustic Noise | <50db at 1M |
| PHYSICAL | |
| Rack Height | 4U |
| Dimension (W*D*H) | 480*440*180mm |

* Harga, spesifikasi, dan ketersediaan bisa berubah dan tidak mengikat

URL : <https://www.citraweb.com/produk/812/>

Informasi lebih lanjut, pemesanan dan pembelian, hubungi: 0274-554444 atau email sales@citraweb.com