

RG-AP720-L Wireless Access Point



Kode : RG-AP720-L
Kategori : Ruijie
Harga : Rp 1.323.000,00

The Ruijie AP720-L is a high performance 802.11ac Wave 2 access point with 2x2 MU-MIMO and concurrent Dual-band design, data rate of up to 1.167Gbps.

***Belum termasuk adaptor dan poe injector**
Produk ini merupakan produk Fix Price. Pembelian produk tidak dapat menggunakan diskon apapun.

- Featuring leading 802.11 ac Wave2.
- Supports 2 spatial streams and delivers up to 300Mbps @2.4G (802.11b/g/n) and 867Mbps @5G (802.11a/n/ac).
- Dual-band performance speeds up to 1.167Gbps per device.
- Totally eliminating Gigabit wireless bottlenecks.



Specification

Model	RG-AP720-L
Radio	Concurrent Dual-band
Protocol	Support concurrent 802.11b/g/n and 802.11a/n/ac
Operating Bands	802.11b/g/n: 2.4 GHz to 2.4835 GHz 802.11a/n/ac: 5.15 GHz to 5.35 GHz, 5.47 GHz to 5.725 GHz, 5.725 GHz to 5.85G (Depending on which country the AP is installed)

Antenna	Built-in antenna (2.4G : 3dBi, 5G : 3dBi)
Spatial Streams	2x2
Max Throughput	Up to 300Mbps at 2.4 GHz Up to 867Mbps at 5 GHz 1167Mbps per AP
Service Ports	1 x10/100/1000 Base-T Uplink supports PoE 1 Console Port
Power Supply	802.3af PoE, local power supply, DC 12V/1.5A (optional) (Note: The power adapter is sold as an optional accessory)
Power Consumption	≤ 12.95 W
Operating temperature	10°C to 50°C
Storage temperature	-40°C to 70°C
MTBF	>400,000H
Maximum number of clients	256
Recommended number of clients	40 (8 at 2.4 GHz, 32 at 5 GHz)
Maximum Number of BSSID	32

[Download Datasheet](#)

* Harga, spesifikasi, dan ketersediaan bisa berubah dan tidak mengikat

URL : <https://www.citraweb.com/produk/954/>

Informasi lebih lanjut, pemesanan dan pembelian, hubungi: 0274-554444 atau email sales@citraweb.com