

## RG-RAP2200(F) Reyee Wi-Fi 5 Ceiling Access Point



**Kode** : RG-RAP2200(F)

**Kategori** : Ruijie

**Harga** : Rp 690.000,00

RG-RAP2200(F) Reyee Wi-Fi 5 Indoor Ceiling with Cloud Managed Access Point.

**\*Belum termasuk adaptor dan poe injector**

**Produk ini merupakan produk Fix Price. Pembelian produk tidak dapat menggunakan diskon apapun.**

- Dual-radio performance, up to 1.267Gbps.
- Get better performance with 802.11ac wave 2's MU-MIMO technology.
- Support to optimize the entire wireless network with just one click.
- Easily set up your Wi-Fi network with Ruijie Cloud APP in 3 minutes.
- With Ruijie Cloud, easy to maintain your networks remotely.



### Specification

<b>Model</b>	RG-RAP2200(F)
<b>Radio</b>	Dual-stream dual-band
<b>Protocol</b>	Wi-Fi 5 (IEEE 802.11ac Wave 2/Wave1) Wi-Fi 4(IEEE 802.11n) 802.11a/b/g
<b>Operating Bands</b>	802.11b/g/n : 2.4 GHz - 2.4835 GHz 802.11a/n/ac : 5 GHz: 5.150 GHz - 5.350 GHz, 5.725 GHz-5.850 GHz
<b>Antenna</b>	Built-in Omnidirectional Antennas (2.4 GHz: 2dBi, 5 GHz: 2dBi)
<b>Spatial Streams</b>	2.4 GHz: 2x2 MIMO 5 GHz: 2x2 MIMO
<b>Max Throughput</b>	Up to 400 Mbps at 2.4 GHz Up to 867 Mbps at 5 GHz 1.267 Mbps per AP
<b>Service Ports</b>	2 x10/100M Base-T LAN1 port supports PoE
<b>Power Supply</b>	802.3af/802.3at PoE, local power supply, DC 12V/1.5A (Note: The power adapter is sold as an optional accessory)
<b>Power Consumption</b>	≤ 12.95 W
<b>Operating temperature</b>	0°C?40°C
<b>Storage temperature</b>	-40°C?70°C
<b>MTBF</b>	>400000H
<b>Operating Mode</b>	AP mode and routing mode
<b>Maximum number of clients</b>	110
<b>Recommended number of clients</b>	40 (8 at 2.4 GHz, 32 at 5 GHz)
<b>Maximum Number of SSIDs</b>	8

[Download Datasheet](#)

*\* Harga, spesifikasi, dan ketersediaan bisa berubah dan tidak mengikat*

**URL :** <https://www.citraweb.com/produk/955/>

**Informasi lebih lanjut, pemesanan dan pembelian, hubungi: 0274-554444 atau email [sales@citraweb.com](mailto:sales@citraweb.com)**

[www.citraweb.com](http://www.citraweb.com)