

On Line UPS PlusPRO 1 2000VA/1800Watt

**Kode** : PLUSPRO1-2000G(B)**Brand** : Aplus**Jenis** : UPS**Harga** : Rp 4.520.000,00

Rp 5.930.000,00

PlusPro 1-2000G adalah produk dari APlus UPS System dengan rating 2000VA/1800Watt yang memiliki desain tower dan juga fitur "Easy Battery Extender".
Dilengkapi dengan external battery connector (Anderson connector) sehingga memungkinkan pengguna untuk mudah melakukan penambahan battery jika menginginkan backup time lebih lama.

***Penjualan produk ini termasuk battery**

***Pengiriman hanya jalur darat dan area pulau jawa**

***Garansi 1 Tahun**

***Garansi battery 1 bulan**

Penawaran Harga Spesial

 08112039555

Features :

- High-performance true double-conversion On-Line UPS 2000VA
- External battery connector (Anderson Connector) to extend the backup time
- Microprocessor control guarantees high reliability
- Low heat dissipation in long-time operation
- Emergency power-off function (EPO)
- USB multiple communications
- Automatic self-testing function
- High-efficiency mode (ECO mode)
- Output voltage regulation +/- 2%
- Power management software
- Output power factor 0.9
- Wide input range
- Fan speed control
- DC start







Battery Type :

- VRLA 12V/9AH or VRLA 12V/7.2AH
- 4 pcs (VRLA 12V/9AH included)
- **Battery dimension 151 x 65 x 100 mm**

Specification :

Model	2KVA
Power	2000VA
Input	
Normal Current (@230V/battery recharged fully)	8.7A
Voltage Range	100~300VAC
Frequency Range	45 ~ 55Hz @ 50Hz system 54 ~ 66Hz @ 60Hz system
Current Distortion(THDi)	<5% (typical) @ 100% linear load
Output	
Voltage	200/208/220/230/240 ± 2%
Frequency (battery mode)	50/60Hz ± 0.05Hz
Current Crest Ratio	3:01
Voltage Distortion (THDv)	< 1% @ linear load, < 5% @ non-linear load
Output Waveform	Pure sine wave
Efficiency	
Inverter Mode	> 90%
ECO Mode	> 97%
Battery	
Rated Battery Voltage	48VDC
Battery Type	12V/9AH
Number of Internal Battery	4
Backup Time (@ Full Load)	> 3.5 mins
Recharge Time (to 90%)	4 hours

Ambient Temperature	0°C ~ 40°C
Storage Temperature	-25°C ~ 55°C
Noise Level	40dB @1 meter
Altitude	< 1000m
	(The load no derating)
	1000m < Altitude ≤ 3000m
	(The load should derating 1 % for every up 100m)
Relative Humidity	<95%

External Battery Installation :



- 48VDC Battery (Recommendation VRLA type Battery)

Manual :

[PLUSPRO1-Manual](#)

* Harga, spesifikasi, dan ketersediaan bisa berubah dan tidak mengikat

URL : <https://www.citraweb.com/produk/964/>

Informasi lebih lanjut, pemesanan dan pembelian, hubungi: 0274-554444 atau email sales@citraweb.com

www.citraweb.com