

FD514GB-X-R410

4GE XPON ONU



High Speed CPU



Low Power Consumption




Software Customization



Optional Shell Supply

Brief Views


FD514GB-X-R410 is an indoor fiber broadband access terminal. The device provides one GPON / EPON adaptive optical port and supports XPON mode. It can be used in connection with our company FD16/17 series GPON OLT or FD12 / 13 series EPON OLT. It can also interconnect with the mainstream manufacture (Huawei / ZTE / Fiberhome) GPON or EPON OLT to provide users with Internet service based on GPON and EPON technology.



Functional Feature

- In compliant with IEEE802.3ah and ITU - T G.984 standard
- Support ONU auto-discovery/Link detection/remote upgrade of software
- Support SN and LOID+Password multiple registration methods
- Support port-based rate limitation and bandwidth control
- Support broadcasting storm resistance function
- Support Dynamic Bandwidth Allocation (DBA)
- EMS network management based on SNMP ,convenient for maintenance
- Support power-off alarm function ,easy for link problem detection
- Single-fiber access, provides internet service.

Product Interface and LED



LED Definitions

Indicator		Description
PWR	Power status	On: The ONT is power on; Off: The ONT is Power off;
PON	ONT Register	On: Success to register to OLT; Blinking: In process of registering to OLT; Off:Failed to register to OLT or no normal optical signal input;
LOS	PON optical signals	On: Optical power lower than receiver sensitivity; Off: Optical in normal;
LAN	LAN port status	On: Ethernet connection is normal; Blinking: Data is being transmitted through the Ethernet port; Off: Ethernet connection is not set up;

RSV	NOT DEFINED	Reserved LED
-----	-------------	--------------

Product Specification

Mechanics

Dimensions	150mm(L) x 115mm(W) x 30mm (H)
Weight	about 500g

Hardware

User Port (LAN)	RJ-45 connector		
	4 *10/100/1000Mbps adaptive Ethernet port		
	Full/half duplex		
	Auto MDI/MDI-X		
Indicators	PWR / PON / LOS / LAN / RSV		
PON Port	PON Mode	EPON: 1000BASE-PX20+ symmetric GPON: FSAN G.984.2 standard, Class B+	
	PON Rate	EPON: 1.25Gbps downstream/upstream GPON: 2.488Gbps/1.244Gbps downstream/upstream	
	Wavelength	Transmit: 1310nm	Receiver: 1490nm
	Receiving sensitivity	EPON: -27dBm	GPON: -28dBm
	Saturated power	EPON: -3dBm	GPON: -8dBm
	Transmitting power	EPON: 0~4dBm	GPON: 0.5~5dBm

Environment

Working temperature	-30 to 65°C
Operating humidity	10% ~ 90% (Non-condensing)

Power

External 12VDC/1A power supply adapter
--

Copyright © Shenzhen C-Data Technology Co., Ltd. 2023. All rights reserved.

Without the prior written consent of C-DATA, any reproduction, excerpting, backup, modification, translation or any other form of commercial use of this document or any portion of this document, and in any form or by any means, to transmit the document are prohibited.

